



INSPIRE
Infrastructure for Spatial Information in
Europe

INSPIRE Metadata Implementing Rules: Technical Guidelines based on EN ISO 19115 and EN ISO 19119

Title	INSPIRE Metadata Implementing Rules: Technical Guidelines based on EN ISO 19115 and EN ISO 19119
Creator	Drafting Team Metadata and European Commission Joint Research Centre
Creation date	2007-10-26
Date of last revision	2009-02-18
Subject	INSPIRE Implementing Rules for Metadata
Status	V. 1.1
Publisher	European Commission Joint Research Centre
Type	Text
Description	Guidelines based on EN ISO 19115 and EN ISO 19119 for Commission Regulation (EC) No 1205/2008 of 3 December 2008 implementing Directive 2007/2/EC of the European Parliament and of the Council as regards metadata
Contributor	See Acknowledgements
Format	Pdf
Source	European Commission Joint Research Centre
Rights	Public
Identifier	MD_IR_and_ISO_20090218
Language	EN
Relation	Not applicable
Coverage	Not applicable

Table of Contents

Acknowledgements	4
Introduction	5
Changes from Version 1.0 of 2008-12-19	5
Normative references	6
1 INSPIRE profile of ISO 19115 and ISO 19119	7
1.1 ISO Core Metadata Elements	7
1.1.1 Spatial dataset and spatial dataset series	7
1.1.2 Services	8
1.1.3 Conclusion	10
1.2 INSPIRE specific constraints	10
1.3 Extensions	11
1.3.1 Spatial data service type	11
1.3.2 Classification of spatial data services	11
2 Basic mapping	12
2.1 Introduction	12
2.1.1 Xpath expression	12
2.1.2 ISO Schemas Location	13
2.2 Identification	14
2.2.1 Resource title	14
2.2.2 Resource abstract	15
2.2.3 Resource Type	16
2.2.4 Resource locator	17
2.2.5 Unique resource identifier	18
2.2.6 Coupled resource	19
2.2.7 Resource language	20
2.3 Classification of spatial data and services	21
2.3.1 Topic category	21
2.3.2 Spatial data service type	22
2.4 Keyword	23
2.4.1 Keyword value	24
2.4.2 Originating controlled vocabulary	25
2.5 Geographic location	27
2.5.1 Geographic bounding box	27
2.6 Temporal reference	29
2.6.1 Temporal extent	29
2.6.2 Date of publication	30
2.6.3 Date of last revision	31
2.6.4 Date of creation	32
2.7 Quality and validity	33
2.7.1 Lineage	33
2.7.2 Spatial resolution	34
2.8 Conformity	36
2.8.1 Degree	37
2.8.2 Specification	38
2.9 Constraints related to access and use	40
2.9.1 Limitations on public access	41
2.9.2 Conditions applying to access and use	43
2.10 Responsible organisation	43
2.10.1 Responsible party	44
2.10.2 Responsible party role	45
2.11 Metadata on metadata	46
2.11.1 Metadata point of contact	46
2.11.2 Metadata date	47
2.11.3 Metadata language	48
3 Detailed mapping	49
3.1 Introduction	49
3.2 Resource MetadataSet	49
3.3 Identification Section	50
3.3.1 Sub-elements for spatial dataset and spatial dataset series	50
3.3.2 Sub-elements for service resources	51

3.4	Data Quality Section.....	52
3.4.1	Lineage.....	52
3.4.2	Conformity.....	52
3.5	Responsible Organisation.....	53
3.5.1	Resource responsible organisation.....	53
3.5.2	Metadata point of contact.....	53
3.6	Constraint section.....	53
3.7	Abbreviations.....	54
Annex A	– ISO/TS 19139 encoding of the INSPIRE metadata elements.....	55
A.1	Introduction.....	55
A.2	From the conceptual schema to XML File instances.....	55
A.3	Polymorphism.....	55
A.4	Management of polymorphism.....	55
A.4.1	Management of community extensions.....	55
A.4.2	Parsing of metadata files.....	55
A.5	Management of containment by reference.....	56
A.6	ISO 19139 and multilingual metadata.....	56
A.6.1	The default language.....	57
A.6.2	Alternate languages.....	58
A.6.3	Embedded translations.....	58
A.6.4	Use of translation files.....	59
A.7	Contexts of use.....	60
A.7.1	Use of ISO 19139 in the context of a Catalogue Service.....	60
A.7.2	Use of ISO 19139 in the context of the standard interchange by transfer.....	60
A.8	Character encoding.....	60
A.9	Temporal extent encoding.....	60
A.10	Spatial resolution encoding.....	62
A.11	Codelists.....	63
A.12	Example of ISO 19139 XML Metadata Sets.....	64
A.12.1	Dataset.....	64
A.12.2	Dataset series.....	70
A.12.3	Service.....	70

Acknowledgements

Many individuals and organisations have contributed to the development of these Guidelines.

The Drafting Team on Metadata included: Marcel Reuvers (Netherlands), Nicolas Lesage (France), Kristian Senkler (Germany), Michael Gould (Spain), Gil Ross (UK), Stefano Nativi (Italy), Jan Hjelmager (Denmark), Franz Daffner (European Environment Agency), Per Ryghaud (Norway), Thomas Vögele and Fred Kruse (Germany), David Danko (USA).

The team at the Joint Research Centre who has contributed to these Guidelines include: Massimo Craglia, Ioannis Kanellopoulos, Gianluca Luraschi, Roberto Lucchi, Michael Lutz, Michel Millot, Nicole Ostländer, Angelo Quaglia, Paul Smits.

We are also grateful to Alejandra Sánchez Maganto (Spain) and colleagues for their contribution.

Contact information

Massimo Craglia (Editor)
European Commission Joint Research Centre
Institute for Environment and Sustainability
Spatial Data Infrastructures Unit
TP262, Via Fermi 2749
I-21027 Ispra (VA)
ITALY
E-mail: massimo.craglia@jrc.it
Tel.: +39-0332-786269
Fax: +39-0332-786325

<http://ies.jrc.ec.europa.eu/>
<http://www.jrc.ec.europa.eu/>

Introduction

According to Article 5(4) of Directive 2007/2/EC, the INSPIRE Implementing Rules shall take account of relevant, existing international standards and user requirements. In the context of metadata for spatial data and spatial data services, the standards EN ISO 19115, EN ISO 19119, and ISO 15836 (Dublin Core) have been identified as important standards

Commission Regulation (EC) No. 1205/2008 implementing Directive 2007/2/EC of the European Parliament and of the Council as regards metadata was adopted on 3rd December 2008, and published on the Official Journal of the European Union on 4th December (*OJ L 326, 4.12.2008, p. 12–30*). Any reference in this document to “Implementing Rules for Metadata” refers to the above mentioned Regulation

The aim of this document is to define how the Regulation can be implemented using EN ISO 19115 and EN ISO 19119. The following subsections describe for each element of the Regulation its relation with the mentioned European standards.

The implementation of the Regulation using ISO 15836 is the subject of a separate document.

This is an initial version of this document that will be developed further in collaboration with the stakeholder community and relevant standardization organizations.

This document will be publicly available as a ‘non-paper’, as it does not represent an official position of the Commission, and as such can not be invoked in the context of legal procedures.

Legal Notice

Neither the European Commission nor any person acting on behalf of the Commission is responsible for the use which might be made of this publication.

Changes from Version 1.0 of 2008-12-19

This document is Version 1.1. The changes introduced since Version 1.0 are:

- New paragraph in Section 1.3 (after the bullets)
- Revised introduction to Section 2.9: Constraints related to access and use
- Revised Section 2.9.1: Limitations on public access

Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 19115 designates these two normative references:

- EN ISO 19115:2005, *Geographic information - Metadata*¹
- ISO 19115/Cor.1:2006, *Geographic information – Metadata, Technical Corrigendum 1*

ISO 19119 designates these two normative references:

- ISO 19119:2005, *Geographic information - Services*
- ISO 19119:2005/Amd 1:2008, *Extensions of the service metadata model*

ISO 19108 designates:

- EN ISO 19108:2005, *Geographic information – Temporal Schema*²

ISO 639-2, *Codes for the representation of names of languages - Part 2: Alpha-3 codeda control*

ISO 8601, *Data elements and interchange formats - Information interchange - Representation of dates and times*

ISO/TS 19139:2007, *Geographic information - Metadata – XML Schema Implementation*

CSW2 AP ISO, *OpenGIS Catalogue Services Specification 2.0.2 - ISO Metadata Application Profile*, Version 1.0.0, OGC 07-045, 2007

ISO 10646-1, *Information technology — Universal Multiple-Octet Coded Character Set (UCS) — Part 1: Architecture and Basic Multilingual Plane*

¹ EN ISO 19115:2005 is the adoption by CEN of ISO 19115:2003

² EN ISO 19108:2005 is the adoption by CEN of ISO 19108:2002

1 INSPIRE profile of ISO 19115 and ISO 19119

1.1 ISO Core Metadata Elements

1.1.1 Spatial dataset and spatial dataset series

The table below compares the core requirements of ISO 19115 (see Table 3 in 6.5 of ISO 19115:2003) to the requirements of INSPIRE for spatial dataset and spatial dataset series as defined in the Implementing Rules for metadata.

ISO 19115 Core	INSPIRE	Comments
Dataset title (M)	Part B 1.1 Resource Title	-
Dataset reference date (M)	Part B 5 Temporal Reference	ISO 19115 is more demanding. The metadata shall contain a date of publication, revision or creation of the resource, while in INSPIRE the Temporal Reference can also be expressed through Temporal Extent.
Dataset responsible party (O)	Part B 9 Responsible organisation	INSPIRE is more demanding by mandating both the name of the organisation, and a contact e-mail address
Geographic location of the dataset (C)	Part B 4.1 Geographic Bounding Box	INSPIRE is more restrictive. A Geographic bounding box is mandated
Dataset language (M)	Part B 1.7 Resource Language	ISO 19115 is more demanding. It mandates the dataset language, even if the resource does not include any textual information. The ISO 19115 Dataset language is defaulted to the Metadata language.
Dataset character set (C)	-	ISO 19115 is more demanding. The dataset character set has to be documented in ISO 19115 when ISO 10646-1 is not used.
Dataset topic category (M)	Part B 2.1 Topic Category	-
Spatial resolution of the dataset (O)	Part B 6.2 Spatial Resolution	-
Abstract describing the dataset (M)	Part B 1.2 Resource abstract	-
Distribution format (O)	-	-
Additional extent information for the dataset (vertical and temporal) (O)	Part B 5.1 Temporal extent	INSPIRE is more demanding. A temporal reference is mandated, and can be expressed as a temporal extent.
Spatial representation type (O)	-	-
Reference system (O)	-	-
Lineage (O)	Part B 6.1 Lineage	INSPIRE is more demanding. A general lineage statement is mandated.
On-line resource (O)	Part B 1.4 Resource Locator	-
Metadata file identifier (O)	-	-

ISO 19115 Core	INSPIRE	Comments
Metadata standard name (O)	-	-
Metadata standard version (O)	-	-
Metadata language (C)	Part B 10.3 Metadata Language	INSPIRE is more demanding. The metadata language is mandated even if it is defined by the encoding.
Metadata character set (C)	-	ISO 19115 is more demanding. The metadata character set has to be documented in ISO 19115 when ISO 10646-1 is not used.
Metadata point of contact (M)	Part B 10.1 Metadata point of contact	INSPIRE is more demanding by mandating both the name of the organisation, and a contact e-mail address.
Metadata date stamp (M)	Part B 10.2 Metadata Date	ISO is more restrictive because this element shall contain the "date that the metadata was created" and INSPIRE may contain the "date when the metadata record was created or updated"
-	Part B 1.3 Resource Type	INSPIRE is more demanding
-	Part B 1.5 Unique Resource Identifier	INSPIRE is more demanding
-	Part B 3 Keyword	INSPIRE is more demanding
-	Part B 7 Conformity	INSPIRE is more demanding
-	Part B 8.1 Conditions for access and use	INSPIRE is more demanding
-	Part B 8.2 Limitations on public access	INSPIRE is more demanding

1.1.2 Services

The table below compares the core requirements of ISO 19115 (see Table 3 in 6.5 of ISO 19115:2003) to the requirements of INSPIRE for services as defined in the Implementing Rules for metadata. The greyed lines correspond to core metadata elements not applicable to services.

ISO 19115 Core	INSPIRE	Comments
Dataset title (M)	Part B 1.1 Resource Title	-
Dataset reference date (M)	Part B 5 Temporal Reference	ISO 19115 is more demanding. Despite its name, this ISO 19115 Core metadata element applies to services. A reference date of the service (date of publication, revision or creation ...) is mandated.
Dataset responsible party (O)	Part B 9 Responsible organisation	-
Geographic location of the dataset (C)	-	See INSPIRE Geographic Bounding Box

ISO 19115 Core	INSPIRE	Comments
-	Part B 4.1 Geographic Bounding Box	The Geographic Bounding Box is handled in ISO 19119 with a different metadata element from the one corresponding to "Geographic location of the dataset"
Dataset language (M)	-	Not applicable to services
Dataset character set (C)	-	Not applicable to services
Dataset topic category (M)	-	Not applicable to services
Spatial resolution of the dataset (O)	Part B 6.2 Spatial Resolution	In the current version of ISO 19119, it is not possible to express the restriction of a service concerning the spatial resolution
Abstract describing the dataset (M)	Part B 1.2 Resource abstract	-
Distribution format (O)	-	-
Additional extent information for the dataset (O)	-	-
Spatial representation type (O)	-	-
Reference system (O)	-	-
Lineage (O)	-	-
On-line resource (O)	Part B 1.4 Resource Locator	-
Metadata file identifier (O)	-	-
Metadata standard name (O)	-	-
Metadata standard version (O)	-	-
Metadata language (C)	Part B 10.3 Metadata Language	INSPIRE is more demanding. The metadata language is mandated.
Metadata character set (C)	-	ISO 19115 is more demanding. The metadata character set has to be documented in ISO 19115 when ISO 10646-1 is not used.
Metadata point of contact (M)	Part B 10.1 Metadata point of contact	-
Metadata date stamp (M)	Part B 10.2 Metadata Date	ISO is more restrictive because this element shall contain the "date that the metadata was created" and INSPIRE may contain the "date when the metadata record was created or updated"
-	Part B 1.3 Resource Type	INSPIRE is more demanding
-	Part B 1.6 Coupled Resource	Optional in INSPIRE
-	Part B 2.2 Spatial Data Service Type	INSPIRE is more demanding

ISO 19115 Core	INSPIRE	Comments
	Part B 3 Keyword	INSPIRE is more demanding
-	Part B 7 Conformity	INSPIRE is more demanding
-	Part B 8.1 Conditions for access and use	INSPIRE is more demanding
-	Part B 8.2 Limitations on public access	INSPIRE is more demanding

1.1.3 Conclusion

- The conformance of an ISO 19115 metadata set to the ISO 19115 Core does not guarantee the conformance to INSPIRE;
- The use of these guideline to create INSPIRE metadata ensures that the metadata is not in conflict with ISO 19115. However, full conformance to ISO 19115 implies the provision of additional metadata elements which are not required by INSPIRE.

Over the structural requirements formalised through the mappings, the conformance to INSPIRE is also a matter of semantic of the information provided. If it is acceptable that the ISO 19115/ISO 19119 contain information which are not strictly bounded to the definition of the corresponding INSPIRE metadata elements, the minimum requirements expressed in the implementing rules have also to be met semantically, i.e. with metadata contents strictly satisfying the INSPIRE requirements.

1.2 INSPIRE specific constraints

Here is an initial list of INSPIRE constraints applicable to an ISO 19115/ISO 19119 metadata set (i.e. an instance of MD_Metadatas) describing a resource:

- SC1. MD_Metadatas.language is mandatory;
- SC2. MD_Metadatas.hierarchyLevel is mandatory;
- SC3. INSPIRE only considers the first instance of MD_Metadatas.hierarchyLevel (i.e. MD_Metadatas.hierarchyLevel[1]) when there are many;
- SC4. If the value of MD_Metadatas.hierarchyLevel[1] is not **service**, **dataset** or **series**, the metadata set is out of scope of the directive;
- SC5. When there are many instances of MD_Metadatas.identificationInfo, only the first one (i.e. MD_Metadatas.identificationInfo[1]) concerns the current INSPIRE Resource;
- SC6. INSPIRE only considers the instance of MD_Metadatas.dataQualityInfo applicable to the whole resource;
- SC7. There shall not be more than one instance of MD_Metadatas.identificationInfo[1].MD_Identifier.citation.CI_Citation.date declared as a creation date (i.e. CI_Date.dateType having the creation value);
- SC8. MD_Metadatas.identificationInfo[1].MD_DataIdentification.citation.CI_Citation.identifier is mandatory for metadata sets related to spatial dataset and spatial dataset series;
- SC9. The data type of MD_Metadatas.identificationInfo.MD_DataIdentification.language is the codelist LanguageCode from ISO/TS 19139;
- SC10. There is at least one instance of MD_Metadatas.identificationInfo[1].MD_DataIdentification.extent defining the geographic location of the resource as a geographic bounding box (i.e. an instance of EX_GeographicBoundingBox or one of its subclasses).
- SC11. MD_Metadatas.identificationInfo[1].SV_ServiceIdentification.operatesOn shall be instantiated by reference
- SC12. There shall be at least one instance of MD_Metadatas.identificationInfo[1].MD_Identifier.resourceConstraints

- SC13. The coordinates of the bounding boxes (instance of EX_GeographicBoundingBox) shall be expressed in any geographic coordinate reference system with the **Greenwich Prime Meridian**
- SC14. For datasets and series:
 MD_Metadata.identificationInfo[1].MD_DataIdentification.pointOfContact[1].CI_ResponsibleParty.organisationName and
 MD_Metadata.identificationInfo[1].MD_DataIdentification.pointOfContact[1].CI_ResponsibleParty.contactInfo.CI_Contact.address.CI_Address.electronicMailAddress are mandatory.
 For services these elements are also mandatory but they are referred as follows:
 MD_Metadata.identificationInfo[1].SV_ServiceIdentification.pointOfContact[1].CI_ResponsibleParty.organisationName and
 MD_Metadata.identificationInfo[1].SV_ServiceIdentification.pointOfContact[1].CI_ResponsibleParty.contactInfo.CI_Contact.address.CI_Address.electronicMailAddress.
- SC15. MD_Metadata.contact[1].CI_ResponsibleParty.organisationName and
 MD_Metadata.contact[1].CI_ResponsibleParty.contactInfo.CI_Contact.address.CI_Address.electronicMailAddress are mandatory.
- SC16. The value of MD_Metadata.contact[1].CI_ResponsibleParty.role.CI_RoleCode shall be pointOfContact.
- SC17. For datasets and series at least one keyword of GEMET thesaurus shall be documented using
 MD_Metadata.identificationInfo[1].MD_DataIdentification.descriptiveKeywords.
- SC18. For services at least one keyword of Part D.4 of INSPIRE shall be documented using
 MD_Metadata.identificationInfo[1].SV_ServiceIdentification.descriptiveKeywords

1.3 Extensions

1.3.1 Spatial data service type

For spatial data service types, the Implementing Rules mandate the use of the value domain of Part D 3. This information is handled using the serviceType attribute (See 2.3.2) of the class SV_ServiceIdentification (See ISO 19119).

The Table below defines the values of the serviceType property. In brackets are the language neutral names to be used.

SPATIAL DATA SERVICE TYPE
Discovery Service (discovery)
View Service (view)
Download Service (download)
Transformation Service (transformation)
Invoke Spatial Data Service (invoke)
Other Services (other)

1.3.2 Classification of spatial data services

For classification of spatial data services, the Implementing Rules mandate the use of the value domain of Part D 4. In order to ensure a language independent expression of the classification of spatial data services, the language neutral name to be used as the value of the ISO 19115 keywords (See 2.4).

2 Basic mapping

2.1 Introduction

The following tables describe the mapping between the metadata elements of INSPIRE, as defined in the INSPIRE implementing rules for metadata, and ISO 19115/ISO 19119. For each of the INSPIRE Metadata element, the mapping is composed of:

- The main characteristics of the metadata element as they are defined³ in the INSPIRE implementing rules (**IR**) for metadata, i.e.:
 - The reference to the paragraph of the implementing rules describing the metadata element;
 - The name of the metadata element as used in the implementing rules;
 - The **obligation/condition** applicable to the metadata element;
 - The **multiplicity** of the metadata element.
- The main characteristics of the corresponding metadata element of **ISO 19115** or **ISO 19119**, i.e.:
 - The **number** that identifies the metadata element inside tables in ISO 19115 (or ISO 19119) published standard;
 - The **name** by which the metadata element is known in ISO 19115 (or ISO 19119) published standard;
 - The **definition**, which gives the current ISO 19115 or ISO 19119 terms for describing the metadata element (Annex B of ISO 19115 standard: Data Dictionary for geographic metadata or Annex C of ISO 19119: Data dictionary for geographic service metadata);
 - An **XPath** expression indicating the metadata element within the ISO 19115 / ISO 19119 UML model (see 2.1.1).
 - An **example** that illustrates the description of the metadata element by providing a concrete case.
- **Some Implementing instructions**, which give more warnings about the implementation in the particular context of the current metadata element.
- **An example of XML encoding**, i.e. a fragment of the XML of a metadata record created and validated with the INSPIRE Metadata Editor available from the EU Geoportal (<http://www.inspire-geoportal.eu/inspireEditor.htm>).

The overall structure of an ISO 19115/ISO 19119 metadata set supporting the requirements expressed in the INSPIRE Implementing rules for metadata is defined in Section 3 of this document.

2.1.1 Xpath expression

This compact notation allows many defaults and abbreviations for common cases. The simplest XPath takes a form such as `/A/B/C` which selects C elements that are children of B elements that are children of the A element that forms the outermost element of the model. More complex expressions can be constructed by specifying an axis other than the default 'child' axis, a node test other than a simple name, or predicates, which can be written in square brackets after any step. The main rules are the following ones:

- `*` selects all element children of the context node;
- `text()` selects all text node children of the context node;
- `@name` selects the name attribute of the context node;
- `@*` selects all the attributes of the context node;
- `.` selects the context node;
- `//para` selects the para element descendants at any level of the context node;
- `..` selects the parent of the context node.

³ In case of discrepancy, the INSPIRE Implementing rules take precedence

Hereafter, the root element of the XPath expression is an instance of MD_Metadata or one of its subclass. The possible subelements of a class are its properties. The possible subelement of a property is its data type or a subtype of its data type. In order to manage the polymorphism, the XPath expression deals with the data type in a generic way (e.g., `property_element_name/*/datatype_property_name`).

2.1.2 ISO Schemas Location

Official ISO schemas (ISO AP or ISO 19139) are currently found in two separate locations:

1) ISO repository for public available standards.

The ISO 19139 schemas can be found here:

http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/

Date of schemas: 2007-08-11.

2.) OGC Schema repository

The ISO 19139 schemas are located here: <http://schemas.opengis.net/iso/19139/20070417/>

Date of schemas: 2007-04-17.

and here: <http://schemas.opengis.net/iso/19139/20060504/>

Date of schemas: 2006-06-04.

ISO AP schemas are located here:

<http://schemas.opengis.net/csw/2.0.2/profiles/apiso/>

Date of schemas: 2007-07-19.

The ISO AP schemas are bound to <http://schemas.opengis.net/iso/19139/20060504/>

The difference in the schemas located in the OGC repository is the GML version. The version dated "2007-04-17" uses GML 3.2.1, the version dated "2006-06-04" use GML 3.2.0. The version "2006-06-04" provides gml in a separate directory (/gml) whereas the version "2007-04-17" directly refers to <http://schemas.opengis.net/gml/3.2.1/>. The major difference is that GML 3.2.0 schemas are defined in the namespace <http://www.opengis.net/gml> whereas GML 3.2.1 schemas are defined in the namespace <http://www.opengis.net/gml/3.2>.

The schemas located in the ISO repository for public available standards are comparable to OGC schemas located here: <http://schemas.opengis.net/iso/19139/20070417/>.

In conclusion:

To Validate XML against ISO AP 1.0:

<http://schemas.opengis.net/csw/2.0.2/profiles/apiso/1.0.0/apiso.xsd>

To Validate XML against ISO 19139 with GML 3.2.0:

<http://schemas.opengis.net/iso/19139/20060504/gmd/gmd.xsd>

To Validate XML against ISO 19139 with GML 3.2.1:

http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/gmd/gmd.xsd or
<http://schemas.opengis.net/iso/19139/20070417/gmd/gmd.xsd>

2.2 Identification

2.2.1 Resource title

IR	Reference	Part B 1.1
	Element name	Resource title
	Obligation / condition	Mandatory
	Multiplicity	[1]
ISO 19115	Number	360
	Name	title
	Definition	Name by which the cited resource is known.
	XPath	identificationInfo[1]/*/citation/*/title
	Data type	CharacterString
	Domain	Free text
	Example	Image2000 Product 1 (nI2) Multispectral
Implementing instructions		None

Example of XML encoding:

```
<gmd:MD_Metadata ...  
...  
  <gmd:identificationInfo>  
    <gmd:MD_DataIdentification>  
      <gmd:citation>  
        <gmd:CI_Citation>  
          <gmd:title>  
            <gco:CharacterString>Image2000 Product 1 (nI2)  
Multispectral</gco:CharacterString>  
          </gmd:title>  
          </gmd:CI_Citation>  
        </gmd:citation>  
      </gmd:MD_DataIdentification>  
    </gmd:identificationInfo>  
...  
</gmd:MD_Metadata>
```

2.2.2 Resource abstract

IR	Reference	Part B 1.2
	Element name	Resource abstract
	Obligation / condition	Mandatory
	Multiplicity	[1]
ISO 19115	Number	25
	Name	abstract
	Definition	Brief narrative summary of the content of the resource(s).
	XPath	identificationInfo[1]*/abstract
	Data type	CharacterString
	Domain	Free text
	Example	IMAGE2000 product 1 individual orthorectified scenes. IMAGE2000 was produced from ETM+ Landsat 7 satellite data and provides a consistent European coverage of individual orthorectified scenes in national map projection systems. The year 2000 was targeted as reference year, but a deviation of maximum 1-year was allowed to obtain a full coverage of Europe, which involves approximately 450 Landsat TM Frames. Where Landsat 7 data were not available, Landsat 5 data have been used instead. The spatial resolution is 25 metres for multispectral and 12.5 metres for panchromatic imagery.
Implementing instructions	None	

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
    <gmd:MD_DataIdentification>
...
      <gmd:abstract>
        <gco:CharacterString>IMAGE2000 product 1 individual orthorectified scenes.
IMAGE2000 was produced from ETM+ Landsat 7 satellite data and provides a consistent
European coverage of individual orthorectified scenes in national map projection systems.
The year 2000 was targeted as reference year, but a deviation of maximum 1-year was
allowed to obtain a full coverage of Europe, which involves approximately 450 Landsat TM
Frames. Where Landsat 7 data were not available, Landsat 5 data have been used instead.
The spatial resolution is 25 metres for multispectral and 12.5 metres for panchromatic
imagery.
        </gco:CharacterString>
      </gmd:abstract>
...
    </gmd:MD_DataIdentification>
  </gmd:identificationInfo>
...
</gmd:MD_Metadata>

```

2.2.3 Resource Type

IR	Reference	Part B 1.3
	Element name	Resource Type
	Obligation / condition	Mandatory
	Multiplicity	[1]
ISO 19115	Number	6
	Name	hierarchyLevel
	Definition	Scope to which metadata applies.
	XPath	hierarchyLevel
	Data type	MD_ScopeCode
	Domain	CodeList (See Annex B of ISO 19115)
	Example	dataset
Implementing instructions	<p>The values of MD_ScopeCode in the scope of the directive (See SC4 in 1.2) are:</p> <ul style="list-style-type: none"> • dataset for spatial datasets; • series for spatial dataset series; • service for spatial data services. <p>The hierarchyLevel property is not mandated by ISO 19115, but is mandated for conformance to the INSPIRE Metadata Implementing rules (See SC2 in 1.2).</p>	

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:hierarchyLevel>
    <gmd:MD_ScopeCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resou
rces/Codelist/gmxCodelists.xml#MD_ScopeCode" codeListValue="dataset">
      dataset
    </gmd:MD_ScopeCode>
  </gmd:hierarchyLevel>
...
</gmd:MD_Metadata>

```


2.2.4 Resource locator

IR	Reference	Part B 1.4
	Element name	Resource locator
	Obligation / condition	<ul style="list-style-type: none"> Conditional for spatial dataset and spatial dataset series: Mandatory if a URL is available to obtain more information on the resources and/or access related services. Conditional for services: Mandatory if linkage to the service is available
	Multiplicity	[0..*]
ISO 19115	Number	397
	Name	linkage
	Definition	Location (address) for on-line access using a Uniform Resource Locator address or similar addressing scheme.
	XPath	distributionInfo/*/transferOptions/*/onLine/*/linkage
	Data type	URL
	Domain	URL (IETF RFC1738 and IETF RFC 2056)
	Example	http://image2000.jrc.it
Implementing instructions	<ul style="list-style-type: none"> Specify a valid URL to the resource. If no direct link to a resource is available, provide link to a contact point where more information about the resource is available. For a service, the Resource Locator might be one of the following: <ul style="list-style-type: none"> - A link to the service capabilities document; - A link to the service WSDL document (SOAP Binding); - A link to a web page with further instructions - A link to a client application that directly accesses the service 	

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:distributionInfo>
    <gmd:MD_Distribution>
...
      <gmd:transferOptions>
        <gmd:MD_DigitalTransferOptions>
          <gmd:onLine>
            <gmd:CI_OnlineResource>
              <gmd:linkage>
                <gmd:URL>http://image2000.jrc.it/</gmd:URL>
              </gmd:linkage>
            </gmd:CI_OnlineResource>
          </gmd:onLine>
        </gmd:MD_DigitalTransferOptions>
      </gmd:transferOptions>
    </gmd:MD_Distribution>
  </gmd:distributionInfo>
...
</gmd:MD_Metadata>

```

2.2.5 Unique resource identifier

IR	Reference	Part B 1.5
	Element name	Unique resource identifier
	Obligation / condition	Mandatory for dataset and dataset series.
	Multiplicity	[1..*]
ISO 19115	Number	365
	Name	Identifier
	Definition	value uniquely identifying an object within a namespace.
	XPath	identificationInfo[1]/*/citation/*/identifier
	Data type	MD_Identifier
	Domain	See B.2.7.3 of ISO 19115. The code property is required at a minimum, and a codeSpace property may be provided.
	Examples	code: http://image2000.jrc.it#image2000_1_nl2_multi code: image2000_1_nl2_multi codeSpace: http://image2000.jrc.it code: 527c4cac-070c-4bca-9aaf-92bece7be902
Implementing instructions	If a codeSpace is provided, the data type to be used is RS_Identifier. If the dataset is coupled to a service, the value of the "id" attribute assigned to the MD_DataIdentification element should correspond to the code of one of the Unique Resource Identifiers (2.2.6 Coupled resource).	

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
    <gmd:MD_DataIdentification id="image2000_1_nl2_multi" >
      <gmd:citation>
        <gmd:CI_Citation>
          ...
            <gmd:identifier>
              <gmd:RS_Identifier>
                <gmd:code>
<gco:CharacterString>image2000_1_nl2_multi</gco:CharacterString>
                </gmd:code>
              <gmd:codeSpace>
<gco:CharacterString>http://image2000.jrc.it</gco:CharacterString>
              </gmd:codeSpace>
            </gmd:RS_Identifier>
          </gmd:identifier>
        </gmd:CI_Citation>
      </gmd:citation>
    </gmd:MD_DataIdentification>
  </gmd:identificationInfo>
...
</gmd:MD_Metadata>

```

2.2.6 Coupled resource

IR	Reference	Part B 1.6
	Element name	Coupled resource
	Obligation / condition	<ul style="list-style-type: none"> Not applicable to dataset and dataset series Conditional to services: Mandatory if linkage to datasets on which the service operates are available.
	Multiplicity	[0..*]
ISO 19119	Number	9 of C.2.2
	Name	identificationInfo[1]*/operatesOn
	Definition	Provides information about the datasets that the service operates on.
	XPath	identificationInfo[1]*/operatesOn
	Data type	MD_DataIdentification
	Domain	A unique resource identifier or locator of the MD_DataIdentification object.
	Example	http://image2000.jrc.it#image2000_1_n12_multi
Implementing instructions	<p>The property shall be implemented by reference (See SC11 in 1.2). For consistency, the value of the “id” attribute assigned to the referenced MD_DataIdentification element should correspond to the code of one of the Unique Resource Identifiers defined for the coupled resource (see 2.2.5 Unique resource identifier)</p>	

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
    <srv:SV_ServiceIdentification>
...
      <srv:operatesOn xlink:href="http://image2000.jrc.it#image2000_1_n12_multi"/>
    </srv:SV_ServiceIdentification>
...
  </gmd:identificationInfo>
...
</gmd:MD_Metadata>

```

2.2.7 Resource language

IR	Reference	Part B 1.7																								
	Element name	Resource language																								
	Obligation / condition	<ul style="list-style-type: none"> Conditional for spatial dataset and spatial dataset series: Mandatory if the resource includes textual information. Not applicable to services. 																								
	Multiplicity	[0..*]																								
ISO 19115	Number	39																								
	Name	language																								
	Definition	Language(s) used within the datasets																								
	XPath	identificationInfo[1]*/language																								
	Data type	LanguageCode (ISO/TS 19139)																								
	Domain	<p>Codelist (See ISO/TS 19139) based on alpha-3 codes of ISO 639-2. Use only three-letter codes from in ISO 639-2/B (bibliographic codes), as defined at http://www.loc.gov/standards/iso639-2/</p> <p>The list of codes for the 23 official EU languages is:</p> <table> <tr> <td>Bulgarian – bul</td> <td>Italian – ita</td> </tr> <tr> <td>Czech – cze</td> <td>Latvian – lav</td> </tr> <tr> <td>Danish – dan</td> <td>Lithuanian – lit</td> </tr> <tr> <td>Dutch – dut</td> <td>Maltese – mlt</td> </tr> <tr> <td>English – eng</td> <td>Polish – pol</td> </tr> <tr> <td>Estonian – est</td> <td>Portuguese – por</td> </tr> <tr> <td>Finnish – fin</td> <td>Romanian – rum</td> </tr> <tr> <td>French – fre</td> <td>Slovak – slo</td> </tr> <tr> <td>German – ger</td> <td>Slovenian – slv</td> </tr> <tr> <td>Greek – gre</td> <td>Spanish – spa</td> </tr> <tr> <td>Hungarian – hun</td> <td>Swedish – swe</td> </tr> <tr> <td>Irish – gle</td> <td></td> </tr> </table>	Bulgarian – bul	Italian – ita	Czech – cze	Latvian – lav	Danish – dan	Lithuanian – lit	Dutch – dut	Maltese – mlt	English – eng	Polish – pol	Estonian – est	Portuguese – por	Finnish – fin	Romanian – rum	French – fre	Slovak – slo	German – ger	Slovenian – slv	Greek – gre	Spanish – spa	Hungarian – hun	Swedish – swe	Irish – gle	
	Bulgarian – bul	Italian – ita																								
Czech – cze	Latvian – lav																									
Danish – dan	Lithuanian – lit																									
Dutch – dut	Maltese – mlt																									
English – eng	Polish – pol																									
Estonian – est	Portuguese – por																									
Finnish – fin	Romanian – rum																									
French – fre	Slovak – slo																									
German – ger	Slovenian – slv																									
Greek – gre	Spanish – spa																									
Hungarian – hun	Swedish – swe																									
Irish – gle																										
Example	eng																									
Implementing instructions	An instance of the language property is mandated by ISO 19115 ; it can be defaulted to the value of the Metadata Language when the dataset or the dataset series does not contain textual information.																									

Examples of XML encoding:

1) Most interoperable: the element value repeats the codeListValue

```
<gmd:language>
  <gmd:LanguageCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resou
rces/Codelist/ML_gmxCodelists.xml#LanguageCode" codeListValue="eng">
    eng
  </gmd:LanguageCode>
</gmd:language>
```

2) Most compliant: the element value is the name of the codeListValue expressed in the default language of the Metadata

```
<gmd:language>
  <gmd:LanguageCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resou
rces/Codelist/ML_gmxCodelists.xml#LanguageCode" codeListValue="eng">
    English
  </gmd:LanguageCode>
</gmd:language>
```

2.3 Classification of spatial data and services

2.3.1 Topic category

IR	Reference	Part B 2.1
	Element name	Topic category
	Obligation / condition	<ul style="list-style-type: none"> • Mandatory for datasets and dataset series. • Not applicable to services.
	Multiplicity	[1..*]
ISO 19115	Number	41
	Name	topicCategory
	Definition	Main theme(s) of the dataset
	XPath	identificationInfo[1]/*/topicCategory
	Data type	MD_TopicCategory
	Domain	Enumeration (See B.5.27 of ISO 19115 or Part D 2 of the INSPIRE Implementing Rules for Metadata)
	Example	imageryBaseMapsEarthCover
Implementing instructions	The topic categories defined in Part D 2 of the INSPIRE Implementing rules for metadata are derived directly from the topic categories defined in B.5.27 of ISO 19115. The value of the ISO 19115/ISO 19119 metadata element is the value appearing in the “name” column of the table in B.5.27 of ISO 19115.	

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
    <gmd:MD_DataIdentification>
...
      <gmd:topicCategory>

        <gmd:MD_TopicCategoryCode>imageryBaseMapsEarthCover</gmd:MD_TopicCategory
Code>
      </gmd:topicCategory>
...
    </gmd:MD_DataIdentification>
  </gmd:identificationInfo>
...
</gmd:MD_Metadata>

```

2.3.2 Spatial data service type

IR	Reference	Part B 2.2
	Element name	Spatial data service type
	Obligation / condition	<ul style="list-style-type: none"> • Mandatory for services. • Not applicable to dataset and dataset series.
	Multiplicity	[1]
ISO 19119	Number	1 of C.2.2
	Name	identificationInfo[1]*/serviceType
	Definition	A service type name from a registry of services.
	XPath	identificationInfo[1]*/serviceType
	Data type	GenericName
	Domain	See 1.3.1
Example	view	
Implementing instructions		Use language neutral name from table in 1.3.1

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
    <srv:SV_ServiceIdentification>
...
      <srv:serviceType>
        <gco:LocalName>view</gco:LocalName>
      </srv:serviceType>
...
    </srv:SV_ServiceIdentification>
  </gmd:identificationInfo>
</gmd:MD_Metadata>

```

2.4 Keyword

An INSPIRE Keyword is defined by:

- a keyword value (see 2.4.1), which in ISO is referred to as “Keyword”;
- an optional originating controlled vocabulary (see 2.4.2), which in ISO is referred to as “Thesaurus”.

The INSPIRE Implementing rules for metadata mandate the presence of **at least** one keyword:

- for spatial dataset or spatial dataset series, it shall describe the relevant INSPIRE spatial data theme (as defined in Annex I, II and III of the Directive) originating from the general environmental multilingual thesaurus (GEMET). The titles and definitions of all 34 INSPIRE Spatial Data Themes have now been integrated into the General Environmental Multi-lingual Thesaurus (GEMET) in the 23 official Community languages: See: http://www.eionet.europa.eu/gemet/inspire_themes.
- for spatial data services, it shall at least define the category or subcategory of the service using its language neutral name as defined in Part D 4 of the Metadata Implementing Rules.

In addition to the INSPIRE Spatial Data Theme, also other keywords might be added. These may be described as a free text or may originate from any Controlled Vocabulary. If they originate from a Controlled Vocabulary (Thesaurus, Ontology), for example GEMET or EUROVOC, then the citation of the originating Controlled Vocabulary shall be provided, as described below.

A keyword referring to an INSPIRE Spatial data theme shall be cited as follows:

keyword	title	reference date	date type
hydrography	GEMET - INSPIRE themes, version 1.0	2008-06-01	publication

A keyword originating from GEMET shall be cited as follows:

keyword	title	reference date	date type
freshwater	GEMET - Concepts, version 2.1	2008-06-13	publication

A keyword originating from another thesaurus shall be cited as follows:

keyword	title	reference date	date type
water springs	AGROVOC	2008-04-14	publication

2.4.1 Keyword value

IR	Reference	Part B 3.1
	Element name	Keyword value
	Obligation / condition	Mandatory
	Multiplicity	[1..*]
ISO 19115	Number	53
	Name	keyword
	Definition	Commonly used word(s) or formalised word(s) or phrase(s) used to describe the subject.
	XPath	identificationInfo[1]*/descriptiveKeywords*/keyword
	Data type	CharacterString
	Domain	Free text
	Example	Land cover
Implementing instructions		Each instance of ISO 19115 keyword may originate from a controlled vocabulary described through the thesaurusName property of the instance of descriptiveKeywords to which the keyword pertains.

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
    <gmd:MD_DataIdentification>
...
      <gmd:descriptiveKeywords>
        <gmd:MD_Keywords>
          <gmd:keyword>
            <gco:CharacterString>Land cover</gco:CharacterString>
          </gmd:keyword>
          <gmd:thesaurusName>
... (see next paragraph)
            </gmd:thesaurusName>
          </gmd:MD_Keywords>
        </gmd:descriptiveKeywords>
      </gmd:MD_DataIdentification>
    </gmd:identificationInfo>
...
  </gmd:MD_Metadata>

```


2.4.2 Originating controlled vocabulary

IR	Reference	Part B 3.2
	Element name	Originating controlled vocabulary.
	Obligation / condition	Conditional: Mandatory if the keyword value originates from a controlled vocabulary.
	Multiplicity	[0..1] relative to a single Keyword, but there may be many keywords originating from different controlled vocabularies.
ISO 19115	Number	55
	Name	ThesaurusName
	Definition	Name of the formally registered thesaurus or a similar authoritative source of keywords.
	XPath	identificationInfo[1]/*/descriptiveKeywords/*/thesaurusName
	Data type	CI_Citation
	Domain	The following properties are expected: <ul style="list-style-type: none"> • title of type CharacterString (Free text) • reference date defined as: <ul style="list-style-type: none"> ○ a date type : creation, revision or publication ○ an effective date
Examples	<ul style="list-style-type: none"> • title: "GEMET Thesaurus version 2.1" • date: <ul style="list-style-type: none"> ○ dateType: publication ○ date: 2008-06-13 • title: "AGROVOC" • date: <ul style="list-style-type: none"> ○ dateType: publication ○ date: 2008-04-14 	
Implementing instructions	In order to be consistent with ISO 19115, all the keyword values originating from a single version of a single controlled vocabulary shall be grouped in a single instance of the ISO 19115 descriptiveKeywords property. See also SC17 for datasets and series, and SC 18 for Services.	

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
    <gmd:MD_DataIdentification>
...
      <gmd:descriptiveKeywords>
        <gmd:MD_Keywords>
          <gmd:keyword>
... (see previous paragraph)
          </gmd:keyword>
          <gmd:thesaurusName>
            <gmd:CI_Citation>
              <gmd:title>
                <gco:CharacterString>GEMET - INSPIRE themes, version
1.0</gco:CharacterString>
              </gmd:title>
              <gmd:date>
                <gmd:CI_Date>
                  <gmd:date>
                    <gco>Date>2008-06-01</gco>Date>
                  </gmd:date>

```

```

        <gmd:dateType>
          <gmd:CI_DateTypeCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resou
rces/Codelist/ML_gmxCodelists.xml#CI_DateTypeCode"
codeListValue="publication">publication</gmd:CI_DateTypeCode>
          </gmd:dateType>
        </gmd:CI_Date>
      </gmd:date>
    </gmd:CI_Citation>
  </gmd:thesaurusName>
</gmd:MD_Keywords>
</gmd:descriptiveKeywords>
</gmd:MD_DataIdentification>
</gmd:identificationInfo>
...
</gmd:MD_Metadata>

```

Example of XML encoding for multiple keywords:

```

...
  <gmd:descriptiveKeywords>
    <gmd:MD_Keywords>
      <gmd:keyword>
        <gco:CharacterString>humanGeographicViewer</gco:CharacterString>
      </gmd:keyword>
      <gmd:keyword>
        <gco:CharacterString>satellite imagery</gco:CharacterString>
      </gmd:keyword>
      <gmd:keyword>
        <gco:CharacterString>earth observation</gco:CharacterString>
      </gmd:keyword>
    </gmd:MD_Keywords>
  </gmd:descriptiveKeywords>
...

```

2.5 Geographic location

2.5.1 Geographic bounding box

IR	Reference	Part B 4.1
	Element name	Geographic bounding box
	Obligation/ Condition	<ul style="list-style-type: none"> • Mandatory for spatial dataset and dataset series. • Conditional for spatial services: Mandatory for services with an explicit geographic extent.
	Multiplicity	[1..*] for spatial data sets and spatial dataset series [0..*] for spatial data services
ISO 19115	Number	344
	Name	westBoundLongitude
	Definition	Western-most coordinate of the limit of the dataset extent, expressed in longitude in decimal degrees (positive east).
	XPath	identificationInfo[1]/*/extent*/geographicElement*/westBoundLongitude
	Data type	Decimal
	Domain	$-180.00 \leq \text{westBoundLongitude} \leq 180.00$
	Example	3.93
ISO 19115	Number	345
	Name	eastBoundLongitude
	Definition	Eastern-most coordinate of the limit of the dataset extent, expressed in longitude in decimal degrees (positive east).
	XPath	identificationInfo[1]/*/extent*/geographicElement*/eastBoundLongitude
	Data type	Decimal
	Domain	$-180 \leq \text{eastBoundLongitude} \leq 180.00$
	Example	7.57
ISO 19115	Number	346
	Name	southBoundLatitude
	Definition	Southern-most coordinate of the limit of the dataset extent, expressed in latitude in decimal degrees (positive north).
	XPath	identificationInfo[1]/*/extent*/geographicElement*/southBoundLatitude
	Data type	Decimal
	Domain	$-90.00 \leq \text{southBoundLatitude} \leq \text{northBoundLatitude}$
	Example	52.10
ISO 19115	Number	347
	Name	northBoundLatitude
	Definition	Northern-most coordinate of the limit of the dataset extent, expressed in latitude in decimal degrees (positive north).
	XPath	identificationInfo[1]/*/extent*/geographicElement*/northBoundLatitude
	Data type	Decimal
	Domain	$\text{southBoundLatitude} \leq \text{northBoundLatitude} \leq 90.00$;
	Example	54.10

Implementing instructions	<ul style="list-style-type: none"> • There are as many bounding boxes defining the geographic location of the resource as instances of <code>identificationInfo[1]*/extent*/geographicElement</code> having the <code>westBoundLongitude</code>, <code>eastBoundLongitude</code>, <code>southBoundLatitude</code> and <code>northBoundLatitude</code> properties. The four coordinates of the bounding box originate from the same instance. • The bounding box shall be as small as possible. • The bounding box shall be expressed in decimal degree with a precision of at least 2 decimals • If the bounding box crosses the 180 meridian, then the value of the <code>westBoundLongitude</code> will be greater than the <code>eastBoundLongitude</code> value. • The coordinates of the bounding box are expressed in any geographic coordinate reference system with a Greenwich Prime Meridian (See SC13 in 1.2).
---------------------------	--

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
    <gmd:MD_DataIdentification>
...
      <gmd:extent>
        <gmd:EX_Extent>
          <gmd:geographicElement>
            <gmd:EX_GeographicBoundingBox>
              <gmd:westBoundLongitude>
                <gco:Decimal>3.93</gco:Decimal>
              </gmd:westBoundLongitude>
              <gmd:eastBoundLongitude>
                <gco:Decimal>7.57</gco:Decimal>
              </gmd:eastBoundLongitude>
              <gmd:southBoundLatitude>
                <gco:Decimal>52.10</gco:Decimal>
              </gmd:southBoundLatitude>
              <gmd:northBoundLatitude>
                <gco:Decimal>54.10</gco:Decimal>
              </gmd:northBoundLatitude>
            </gmd:EX_GeographicBoundingBox>
          </gmd:geographicElement>
        </gmd:EX_Extent>
      </gmd:extent>
...
    </gmd:MD_DataIdentification>
  </gmd:identificationInfo>
...
</gmd:MD_Metadata>

```

2.6 Temporal reference

The INSPIRE Implementing Rules for metadata require at least one temporal reference chosen from one of these four categories: temporal extent, data of publication, date of last revision or the date of creation. ISO 19115 is more demanding and requires that at least one of the following is provided: date of publication, the date of last revision or the date of creation. Therefore, whilst providing a temporal extent would suffice to satisfy the INSPIRE Implementing Rules for metadata it is not enough to be compliant with ISO 19115. To be compliant with ISO 19115 it is necessary to use at least one among date of publication, date of last revision, or the date of creation

The default reference system shall be the Gregorian calendar, with dates expressed in accordance with ISO 8601.

2.6.1 Temporal extent

IR	Reference	Part B 5.1
	Element name	Temporal extent
	Obligation / condition	Conditional: At least one temporal reference is required.
	Multiplicity	[0..*] but at least one temporal reference is required.
ISO 19115	Number	351
	Name	Extent
	Definition	Time period covered by the content of the dataset.
	XPath	identificationInfo[1]/*/extent/*/temporalElement/*/extent
	Data type	TM_Primitive ⁴
	Domain	As described in ISO 19108.
	Example	From 1977-03-10T11:45:30 to 2005-01-15T09:10:00
Implementing instructions		Each instance of the temporal extent may be an interval of dates or an individual date. The overall time period covered by the content of the resource may be composed of one or many instances.

Example of XML encoding:

```
<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
    <gmd:MD_DataIdentification>
...
      <gmd:extent>
        <gmd:EX_Extent>
          <gmd:temporalElement>
            <gmd:EX_TemporalExtent>
              <gmd:extent>
                <gml:TimePeriod gml:id="IDd2febbb4-e66f-4ac8-ba76-
8fd9bc7c8be6">
                  <gml:beginPosition>1977-03-10T11:45:30</gml:beginPosition>
                  <gml:endPosition>2005-01-15T09:10:00</gml:endPosition>
                </gml:TimePeriod>
              </gmd:extent>
            </gmd:EX_TemporalExtent>
          </gmd:temporalElement>
        </gmd:EX_Extent>
      </gmd:extent>
...

```

⁴ ISO19108 describes other domains which might support the INSPIRE requirements for temporal metadata. There are no implementations currently known. ISO19108 allows ordinal temporal extents (TM_Position values of TM_OrdinalEras defined within a TM_OrdinalReferenceSystem) and an indeterminate value of "now" is valid under TM_Position. ISO 19108 TM_PeriodDuration also defines the distance in the temporal dimension

```

...
    </gmd:MD_DataIdentification>
...
  </gmd:identificationInfo>
...
</gmd:MD_Metadata>

```

2.6.2 Date of publication

IR	Reference	Part B 5.2
	Element name	Date of publication
	Obligation / condition	Conditional: At least one temporal reference is required.
	Multiplicity	[0..*] but at least one temporal reference is required
ISO 19115	Number	394
	Name	date
	Definition	reference date for the cited resource – publication
	XPath	identificationInfo[1]/*/citation/*/date[./dateType/text()='publication']*/date
	Data type	CI_Date
	Domain	Described in ISO 19108 and ISO 8601
	Example	2007-09-15 or 2007-11-15T11:15:00
Implementing instructions	None	

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
    <gmd:MD_DataIdentification>
      <gmd:citation>
        <gmd:CI_Citation>
...
          <gmd:date>
            <gmd:CI_Date>
              <gmd:date>
                <gco>Date>2007-09-15</gco>Date>
              </gmd:date>
              <gmd:dateType>
                <gmd:CI_DateTypeCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resou
rces/Codelist/ML_gmxCodelists.xml#CI_DateTypeCode"
codeListValue="publication">publication</gmd:CI_DateTypeCode>
                </gmd:dateType>
              </gmd:CI_Date>
            </gmd:date>
...
          </gmd:CI_Citation>
        </gmd:citation>
...
      </gmd:MD_DataIdentification>
...
    </gmd:identificationInfo>
...
  </gmd:MD_Metadata>

```

2.6.3 Date of last revision

IR	Reference	Part B 5.3
	Element name	Date of last revision
	Obligation / condition	Conditional: At least one temporal reference is required
	Multiplicity	[0..1] but at least one temporal reference is required.
ISO 19115	Number	394
	Name	Date
	Definition	reference date for the cited resource – revision
	XPath	identificationInfo[1]/*/citation/*/date[./*/dateType*/text()='revision']*/date
	Data type	Date
	Domain	Described in ISO 19108 and ISO 8601
	Example	2007-09-15 or 2007-11-15T11:15:00
Implementing instructions		There may be more than one revision date provided in an ISO 19115 metadata set, but the INSPIRE date of last revision is the more recent.

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
    <gmd:MD_DataIdentification>
      <gmd:citation>
        <gmd:CI_Citation>
...
          <gmd:date>
            <gmd:CI_Date>
              <gmd:date>
                <gco:DateTime>2007-11-15T11:15:00</gco:DateTime>
              </gmd:date>
              <gmd:dateType>
                <gmd:CI_DateTypeCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmxCodelists.xml#CI_DateTypeCode"
codeListValue="revision">revision</gmd:CI_DateTypeCode>
              </gmd:dateType>
            </gmd:CI_Date>
          </gmd:date>
...
        </gmd:CI_Citation>
      </gmd:citation>
...
    </gmd:MD_DataIdentification>
...
  </gmd:identificationInfo>
...
</gmd:MD_Metadata>

```

2.6.4 Date of creation

IR	Reference	Part B 5.4
	Element name	Date of creation
	Obligation / condition	Conditional: At least one temporal reference is required
	Multiplicity	[0..1] but at least one temporal reference is required
ISO 19115	Number	394
	Name	date
	Definition	reference date for the cited resource – creation
	XPath	identificationInfo[1]/*/citation/*/date[./*/dateType*/text()='creation']*/date
	Data type	Date
	Domain	Described in ISO 19108 and ISO 8601
	Example	2007-09-15 or 2007-11-15T11:15:00
Implementing instructions		If in practice an ISO 19115 metadata set may define more than one creation date, this has no sense. There shall be a single creation date for the resource (See SC7 in 1.2).

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
    <gmd:MD_DataIdentification>
      <gmd:citation>
        <gmd:CI_Citation>
...
          <gmd:date>
            <gmd:CI_Date>
              <gmd:date>
                <gco>Date>2007-09-15</gco>Date>
              </gmd:date>
              <gmd:dateType>
                <gmd:CI_DateTypeCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resou
rces/Codelist/ML_gmxCodelists.xml#CI_DateTypeCode"
codeListValue="creation">creation</gmd:CI_DateTypeCode>
                </gmd:dateType>
              </gmd:CI_Date>
            </gmd:date>
...
          </gmd:CI_Citation>
        </gmd:citation>
...
      </gmd:MD_DataIdentification>
...
    </gmd:identificationInfo>
...
  </gmd:MD_Metadata>

```


2.7 Quality and validity

2.7.1 Lineage

IR	Reference	Part B 6.1
	Element name	Lineage
	Obligation / Condition	<ul style="list-style-type: none"> • Mandatory for spatial dataset and spatial dataset series. • Not applicable to services.
	Multiplicity	[1] for datasets and data set series, [0] for spatial data services
ISO 19115	Number	83
	Name	Statement
	Definition	General explanation of the data producer's knowledge about the lineage of a dataset.
	XPath	dataQualityInfo/*/lineage/*/statement
	Data type	CharacterString
	Domain	Free text
	Example	Product 1 scenes correspond to the path/row of the Landsat orbit.....
Implementing instructions	<ul style="list-style-type: none"> • In addition to general explanation of the data producer's knowledge about the lineage of a dataset it is possible to put data quality statements here. • A single ISO 19115 metadata set may comprise more than one set of quality information, each of them having one or zero lineage statement. There shall be one and only one set of quality information scoped to the full resource and having a lineage statement (See SC6 in 1.2). 	

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
...
  </gmd:identificationInfo>
  <gmd:dataQualityInfo>
    <gmd:DQ_DataQuality>
      <gmd:scope>
...
      </gmd:scope>
      <gmd:report>
...
      </gmd:report>
      <gmd:lineage>
        <gmd:LI_Lineage>
          <gmd:statement>
            <gco:CharacterString>Product 1 scenes correspond to the path/row of the
Landsat orbit. All Image2000 product 1 scenes are ortho-corrected. The ortho-correction
method consisted of using a physical model of the satellite's flight during the scene
acquisition, which was then complemented with Ground Control Points (GCP's) and a Digital
Elevation Model (DEM). Map projection information is attached to the model. The resulting
product has excellent accuracy between the spectral bands, sub-pixel location accuracy
throughout the image and excellent preservation of radiometric characteristics. The geometric
correction was done on a Country basis - according to the relevant national map projection
system(s). A rigorous orbital model was used. Control point measurements were used in a
weighted least squares adjustment to estimate optimal values for the orbital and attitude
parameters. The adjusted parameters were used to resample the raw scene by cubic
convolution in a single step, instead of the usual two step procedure of first producing a
system-corrected scene and then resampling a second time, thus causing unnecessary
smoothing of the data. The final pixel size after resampling is 12.5m for the panchromatic
band, 25m for the multispectral bands and 60m for the thermal band. All the orthorectified

```

```

scenes are well within the requirement of Root Mean Square Error (RMSE) >
25m.</gco:CharacterString>
    </gmd:statement>
  </gmd:LI_Lineage>
</gmd:lineage>
</gmd:DQ_DataQuality>
</gmd:dataQualityInfo>
</gmd:MD_Metadata>

```

2.7.2 Spatial resolution

	Reference	Part B 6.2
	Element name	Spatial resolution
IR	Obligation / Condition	<ul style="list-style-type: none"> • Conditional: Mandatory if an equivalent scale or a resolution distance can be specified. • Conditional: Mandatory when there is a restriction on the spatial resolution for service
	Multiplicity	[0..*]
ISO 19115	Number	60
	Name	equivalentScale
	Definition	level of detail expressed as the scale denominator of a comparable hardcopy map or chart
	XPath	identificationInfo[1]*/spatialResolution*/equivalentScale*/denominator
	Data type	Integer
	Domain	Positive integer
	Example	50000 (e.g. 1:50000 scale map)
ISO 19115	Number	61
	Name	distance
	Definition	Ground sample distance
	XPath	identificationInfo[1]*/spatialResolution*/distance
	Data type	Distance
	Domain	A distance is a Number expressing the distance value and a unit of measure of the distance value.
	Example	25 meters
Implementing instructions	<ul style="list-style-type: none"> • Each spatial resolution is either an equivalent scale OR a ground sample distance. Each spatialResolution element must contain either an equivalent scale or a distance but not both. • When two equivalent scales or two ground sample distances are expressed, the spatial resolution is an interval bounded by these two values. • For services, it is not possible to express the restriction of a service concerning the spatial resolution in the current version of ISO 19119. While the problem is addressed by the standardization community, spatial resolution restrictions for services shall be expressed in the Abstract. 	

Example of XML encoding (equivalentScale):

```

<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
...
    <gmd:MD_DataIdentification>
...
      <gmd:spatialResolution>
        <gmd:MD_Resolution>
          <gmd:distance>
... (see next example)
        </gmd:distance>

```

```

    </gmd:MD_Resolution>
  </gmd:spatialResolution>
</gmd:spatialResolution>
  <gmd:MD_Resolution>
    <gmd:equivalentScale>
      <gmd:MD_RepresentativeFraction>
        <gmd:denominator>
          <gco:Integer>50000</gco:Integer>
        </gmd:denominator>
      </gmd:MD_RepresentativeFraction>
    </gmd:equivalentScale>
  </gmd:MD_Resolution>
</gmd:spatialResolution>
...
  </gmd:MD_DataIdentification>
</gmd:identificationInfo>
...
</gmd:MD_Metadata>

```

Example of XML encoding (distance):

```

<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
...
    <gmd:MD_DataIdentification>
...
      <gmd:spatialResolution>
        <gmd:MD_Resolution>
          <gmd:distance>
            <gco:Distance
uom="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources
/uom/ML_gmxUom.xml#m">25.0</gco:Distance>
          </gmd:distance>
        </gmd:MD_Resolution>
      </gmd:spatialResolution>
    <gmd:spatialResolution>
      <gmd:MD_Resolution>
        <gmd:equivalentScale>
... (see previous example)
        </gmd:equivalentScale>
      </gmd:MD_Resolution>
    </gmd:spatialResolution>
...
  </gmd:MD_DataIdentification>
</gmd:identificationInfo>
...
</gmd:MD_Metadata>

```

2.8 Conformity

In conformance to Directive 2007/2/EC, the metadata shall include information on the degree of conformity with the implementing rules provided in Art. 7-1. ISO 19115 provides a mechanism for reporting about the evaluation of the conformity of the resource against a given specification. This mechanism is used here to handle the conformity requirements of INSPIRE.

The Implementing Rules for metadata defines in Part D 5 three degrees of conformity: conformant, not conformant and not evaluated. In ISO 19115, it is possible to report about the conformity to a specification when it has been evaluated, but the only way to express the fact that the conformity with a given specification has not been evaluated is not to report anything in the metadata.

A precise list of specifications to which the different types of resource have to conform will be mandated later through INSPIRE Implementing Rules for the harmonisation of spatial data sets and services and related instructions. These legal texts will define for each specification the criteria necessary to be conformant, and additional metadata elements for evaluation and use. Once these legal texts are approved, they will be referred to in the metadata using the title of the specification, and the date of publication. At that stage, this Metadata Guidelines document will also be updated accordingly.

When the metadata does not contain any information about one of these specifications, the user applications exploiting the metadata shall report that the conformity to that specification has not been evaluated. So the general process for exploiting the metadata is for each INSPIRE conformity specification to:

- check using the identifier of the quality measure defined for the specification whether the conformance to the specification has been reported;
- report that the conformity to the specification has not been evaluated on this quality measure;
- exploit the metadata, i.e. the description of specification and the degree of conformity, as stated hereafter when the specification has been evaluated.

2.8.1 Degree

IR	Reference	Part B 7.2
	Element name	Degree
	Obligation/Condition	Mandatory
	Multiplicity	[1] understood in the context of a conformity statement when reported in the metadata – there may be more than one conformity statement.
ISO 19115	Number	132
	Name	Pass
	Definition	indication of the conformance result
	XPath	dataQualityInfo/*/report/*/result/*/pass
	Data type	Boolean ⁵
	Domain	<ul style="list-style-type: none"> • true if conformant⁶ • false if not conformant⁵
	Example	true
Implementing instructions		The first two degrees of conformity defined in Part D 5 of the INSPIRE Implementing rules for metadata map to two values of the Boolean domain of ISO 19115. The last value corresponds to the case where no conformance statement is expressed in the metadata for the related specification.

Example of XML encoding

```

<gmd:MD_Metadata ...
...
  <gmd:dataQualityInfo>
    <gmd:DQ_DataQuality>
      <gmd:scope>
...
        </gmd:scope>
        <gmd:report>
          <gmd:DQ_DomainConsistency >
...
            <gmd:result>
              <gmd:DQ_ConformanceResult>
                <gmd:specification>
...
                  </gmd:specification>
                  <gmd:explanation>
                    <gco:CharacterString>See the referenced
specification</gco:CharacterString>
                  </gmd:explanation>
                  <gmd:pass>
                    <gco:Boolean>true</gco:Boolean>
                  </gmd:pass>
                </gmd:DQ_ConformanceResult>
              </gmd:result>
            </gmd:DQ_DomainConsistency>
          </gmd:report>
        <gmd:lineage>
...
          </gmd:lineage>
        </gmd:DQ_DataQuality>
      </gmd:dataQualityInfo>
    </gmd:MD_Metadata>

```

⁶ ISO/TS 19103 defines Boolean as a value defining TRUE or FALSE (EXAMPLE: true or false), while ISO 19115:2003 clearly states that the domain of value of the Boolean properties is 0="no", 1="yes". In the meantime, ISO/TS 19139 implements the Boolean class using the XML build-in type xs:boolean (values are **true** or **false**)

2.8.2 Specification

IR	Reference	Part B 7.1
	Element name	Specification
	Obligation/Condition	Mandatory
	Multiplicity	[1] understood in the context of a conformity statement when reported in the metadata – there may be more than one conformity statement.
ISO 19115	Number	130
	Name	specification
	Definition	citation of the product specification or user requirement against which data is being evaluated.
	XPath	dataQualityInfo/*/report/*/result/*/specification
	Data type	CI_Citation
	Domain	The following properties are expected: <ul style="list-style-type: none"> • title of type CharacterString (Free text); • reference date defined as: <ul style="list-style-type: none"> ○ a date type: creation, revision or publication; ○ an effective date.
Example	<ul style="list-style-type: none"> • title: “INSPIRE Implementing rules laying down technical arrangements for the interoperability and harmonisation of orthoimagery”. • date: <ul style="list-style-type: none"> ○ dateType: publication ○ date: 2011-05-15 	
Implementing instructions	None	

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:dataQualityInfo>
    <gmd:DQ_DataQuality>
      <gmd:scope>
        <gmd:DQ_Scope>
          <gmd:level>
            <gmd:MD_ScopeCode codeListValue="dataset"
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resou
rces/Codelist/gmxCodelists.xml#MD_ScopeCode">dataset</gmd:MD_ScopeCode>
          </gmd:level>
        </gmd:DQ_Scope>
      </gmd:scope>
    <gmd:report>
      <gmd:DQ_DomainConsistency>
        <gmd:result>
          <gmd:DQ_ConformanceResult>
            <gmd:specification>
              <gmd:CI_Citation>
                <gmd:title>
                  <gco:CharacterString>INSPIRE Implementing rules laying
down technical arrangements for the interoperability and harmonisation of
orthoimagery</gco:CharacterString>
                </gmd:title>
                <gmd:date>
                  <gmd:CI_Date>
                    <gmd:date>
                      <gco:Date>2011-05-15</gco:Date>
                    </gmd:date>
                  </gmd:CI_Date>
                </gmd:dateType>
              </gmd:specification>
            </gmd:DQ_ConformanceResult>
          </gmd:result>
        </gmd:DQ_DomainConsistency>
      </gmd:report>
    </gmd:DQ_DataQuality>
  </gmd:dataQualityInfo>

```

```

                                <gmd:CI_DateTypeCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resou
rces/Codelist/ML_gmxCodellists.xml#CI_DateTypeCode"
codeListValue="publication">publication</gmd:CI_DateTypeCode>
                                </gmd:dateType>
                                </gmd:CI_Date>
                                </gmd:date>
                                </gmd:CI_Citation>
                                </gmd:specification>
                                <gmd:explanation>
                                <gco:CharacterString>See the referenced
specification</gco:CharacterString>
                                </gmd:explanation>
                                <gmd:pass>
                                <gco:Boolean>>true</gco:Boolean>
                                </gmd:pass>
                                </gmd:DQ_ConformanceResult>
                                </gmd:result>
                                </gmd:DQ_DomainConsistency>
                                </gmd:report>
                                <gmd:lineage>
...
                                </gmd:lineage>
                                </gmd:DQ_DataQuality>
                                </gmd:dataQualityInfo>
</gmd:MD_Metadata>

```

2.9 Constraints related to access and use

ISO 19115 provides a general mechanism for documenting different categories of constraints applicable to the resource (or its metadata). This mechanism is supported by the class MD_Constraints and its subclasses:

- MD_LegalConstraints for legal constraints;
- MD_SecurityConstraints for security constraints.

There are two major requirements expressed in Directive 2007/2/EC in terms of documentation of the constraints as part of the metadata:

- The conditions applying to access and use of the resource, and where applicable, the corresponding fees as required by Articles 5-2(b) and 11-2(f).
- The limitations on public access: the Member States may limit public access to spatial datasets and spatial data services in a set of cases defined in Article 13. These cases include public security or national defence, i.e. more generally the existence of a security constraint.

Each instance of MD_Constraints expresses:

- Zero or One condition applying to access and use (see 2.9.2);
- Zero or More limitations on public access (see 2.9.1);
- Or, both one or more limitations on public access and a condition applying to access and use.

In any case, there shall be at least one ISO 19115 metadata element representing a limitation on public access (see 2.9.1) and one ISO 19115 metadata element representing a condition applying to access and use (see 2.9.2) as part of the different instances of MD_Constraints and its subclasses.

There shall be at least one instance of MD_Constraints or one of its subclasses (See SC12 in Section 1.2) even if there is no limitation on public access or no specific condition applies to access and use of the resource.⁷ When a single instance is provided in a given metadata set, it shall handle metadata elements representing both at least one condition applying to access and use and at least one limitation on public access in compliance with the mapping provided in 2.9.1 and 2.9.2.

⁷ If the Resource Type is 'service' there might be a conflict with the property 'restrictions' of class 'SV_ServiceIdentification'. This property is also of type MD_Constraints with a multiplicity of 0..1. Any constraint on a service described by this property is out of the scope of the Implementing rules. Instead, the constraints on services shall be defined as stated in clause 2.9.1 and 2.9.2 of this document.

2.9.1 Limitations on public access

IR	Reference	Part B 8.2
	Element name	Limitations on public access
	Obligation/Condition	Mandatory
	Multiplicity	[1..*] for the resource but there are zero or many limitations on public access per instance of MD_Constraints.
ISO 19115	Number	70
	Name	accessConstraints
	Definition	access constraints applied to assure the protection of privacy or intellectual property, and any special restrictions or limitations on obtaining the resource.
	XPath	identificationInfo[1]/*/resourceConstraints/*/accessConstraints
	Data type	MD_RestrictionCode
	Domain	Codelist (strictly limited to the value defined in B.5.24 of ISO 19115)
	Example	intellectualPropertyRights (rights to financial benefit from and control of distribution of non-tangible property that is a result of creativity).
ISO 19115	Number	72
	Name	otherConstraints
	Definition	other restrictions and legal prerequisites for accessing and using the resource or metadata.
	XPath	identificationInfo[1]/*/resourceConstraints/*/otherConstraints
	Data type	CharacterString
	Domain	Free text
	Example	No limitations
ISO 19115	Number	74
	Name	classification
	Definition	name of the handling restrictions on the resource.
	XPath	identificationInfo[1]/*/resourceConstraints/*/classification
	Data type	MD_ClassificationCode
	Domain	Codelist (See B.5.11 of ISO 19115)
	Example	restricted
Implementing instructions	<ul style="list-style-type: none"> • Depending on the instance of MD_Constraints: <ul style="list-style-type: none"> ○ There may be no limitation on public access; ○ There may be only a classification property when expressing a security constraint (i.e., this is an instance of MD_SecurityConstraints or one of its subclasses); ○ There may be one or more instances of the accessConstraints property, possibly associated with one or more instances of otherRestrictions property (i.e, this is an instance of MD_LegalConstraints); • The value of accessConstraints is otherRestrictions, if and only if there are instances of otherConstraints expressing limitations on public access. In such case, the instances of otherConstraints are reported as part of the INSPIRE limitations on public access, but the special value otherRestrictions of accessConstraints should not be reported. This means that the value otherRestrictions is reserved for INSPIRE. This because there is no way to express that the free text contained in otherConstraints is a limitation on public access. 	

Example of XML encoding:

```
<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
    <gmd:MD_DataIdentification>
...
      <gmd:resourceConstraints>
... (see next example)
      </gmd:resourceConstraints>
      <gmd:resourceConstraints>
        <gmd:MD_LegalConstraints>
          <gmd:accessConstraints>
            <gmd:MD_RestrictionCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resou
rces/Codelist/gmxCodelists.xml#MD_RestrictionCode"
codeListValue="otherRestrictions">otherRestrictions</gmd:MD_RestrictionCode>
          </gmd:accessConstraints>
          <gmd:otherConstraints>
            <gco:CharacterString>no limitations</gco:CharacterString>
          </gmd:otherConstraints>
        </gmd:MD_LegalConstraints>
      </gmd:resourceConstraints>
...
    </gmd:MD_DataIdentification>
  </gmd:identificationInfo>
...
</gmd:MD_Metadata>
```

2.9.2 Conditions applying to access and use

IR	Reference	Part B 8.1
	Element name	Condition applying to access and use
	Obligation/Condition	Mandatory
	Multiplicity	[1..*] for the resource but there is zero or one condition applying to access and use per instance of MD_Constraints.
ISO 19115	Number	68
	Name	useLimitation
	Definition	restrictions on the access and use of a resource or metadata
	XPath	identificationInfo[1]/*/resourceConstraints/*/useLimitation
	Data type	CharacterString
	Domain	Free text
	Example	no conditions apply
Implementing instructions	Descriptions of terms and conditions, including where applicable, the corresponding fees shall be provided through this element or a link (URL) where these terms and conditions are described.	

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
    <gmd:MD_DataIdentification>
...
      <gmd:resourceConstraints>
        <gmd:MD_Constraints>
          <gmd:useLimitation>
            <gco:CharacterString>no conditions apply</gco:CharacterString>
          </gmd:useLimitation>
        </gmd:MD_Constraints>
      </gmd:resourceConstraints>
    </gmd:MD_DataIdentification>
  </gmd:identificationInfo>
...
</gmd:MD_Metadata>

```

2.10 Responsible organisation

A responsible organisation is defined by:

- a responsible party (see 2.10.1);
- and a responsible party role (see 2.10.2).

There are one to many responsible organisations for a single resource, but the multiplicity of the responsible and its role are expressed relative to a single responsible organisation.

2.10.1 Responsible party

IR	Reference	Part B 9.1
	Element name	Responsible party
	Obligation/Condition	Mandatory
	Multiplicity	[1] Relative to a responsible organisation, but there may be many responsible organisations for a single resource.
ISO 19115	Number	29
	Name	pointOfContact
	Definition	identification of, and means of communication with, person(s) and organization(s) associated with the resource(s)
	XPath	identificationInfo[1]/*/pointOfContact
	Data type	CI_ResponsibleParty
	Domain	The following properties are expected: <ul style="list-style-type: none"> organisationName : CharacterString contactInfo: <ul style="list-style-type: none"> address: <ul style="list-style-type: none"> electronicMailAddress [1..*] : CharacterString
Example	<ul style="list-style-type: none"> organisationName: SDI Unit, Institute for Environment & Sustainability, Joint Research Centre contactInfo: <ul style="list-style-type: none"> address: <ul style="list-style-type: none"> electronicMailAddress: image2000@jrc.it 	
Implementing instructions	See SC 14.	

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
    <gmd:MD_DataIdentification>
...
      <gmd:pointOfContact>
        <gmd:CI_ResponsibleParty>
          <gmd:organisationName>
            <gco:CharacterString>SDI Unit, Institute for Environment and
Sustainability, Joint Research Centre</gco:CharacterString>
          </gmd:organisationName>
          <gmd:contactInfo>
            <gmd:CI_Contact>
              <gmd:address>
                <gmd:CI_Address>
                  <gmd:electronicMailAddress>
                    <gco:CharacterString>image2000@jrc.it</gco:CharacterString>
                  </gmd:electronicMailAddress>
                </gmd:CI_Address>
              </gmd:address>
            </gmd:CI_Contact>
          </gmd:contactInfo>
          <gmd:role>
... (see next example)
        </gmd:role>
      </gmd:CI_ResponsibleParty>
    </gmd:pointOfContact>
...
  </gmd:identificationInfo>
...
</gmd:MD_Metadata>

```

2.10.2 Responsible party role

IR	Reference	Part B 9.2
	Element name	Responsible party role
	Obligation/Condition	Mandatory
	Multiplicity	[1] relative to a responsible organisation, but there may be many responsible organisations for a single resource.
ISO 19115	Number	379
	Name	role
	Definition	function performed by the responsible party
	XPath	identificationInfo[1]*/pointOfContact*/role
	Data type	CI_RoleCode
	Domain	Codelist (See B.5.5 of ISO 19115)
	Example	custodian
Implementing instructions		There is a direct mapping between the responsible party roles defined in Part D 6 of the INSPIRE Implementing Rules for metadata and the values of the CI_RoleCode codelist of ISO 19115.

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:identificationInfo>
    <gmd:MD_DataIdentification>
...
      <gmd:pointOfContact>
        <gmd:CI_ResponsibleParty>
          <gmd:organisationName>
            <gco:CharacterString>SDI Unit, Institute for Environment and
Sustainability, Joint Research Centre</gco:CharacterString>
          </gmd:organisationName>
          <gmd:contactInfo>
... (see previous example)
          </gmd:contactInfo>
          <gmd:role>
            <gmd:CI_RoleCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resou
rces/Codelist/gmxCodelists.xml#CI_RoleCode"
codeListValue="custodian">custodian</gmd:CI_RoleCode>
          </gmd:role>
          </gmd:CI_ResponsibleParty>
        </gmd:pointOfContact>
...
      </gmd:identificationInfo>
...
</gmd:MD_Metadata>

```

2.11 Metadata on metadata

2.11.1 Metadata point of contact

IR	Reference	Part B 10.1
	Element name	Metadata point of contact
	Obligation/Condition	Mandatory
	Multiplicity	[1..*]
ISO 19115	Number	8
	Name	contact
	Definition	party responsible for the metadata information.
	XPath	contact
ISO 19115	Data type	CI_ResponsibleParty
	Domain	The following properties are expected: <ul style="list-style-type: none"> organisationName : CharacterString contactInfo: <ul style="list-style-type: none"> address: <ul style="list-style-type: none"> electronicMailAddress [1..*] : CharacterString role : CI_RoleCode
ISO 19115	Example	<ul style="list-style-type: none"> organisationName: SDI Unit, Institute for Environment & Sustainability, Joint Research Centre contactInfo: <ul style="list-style-type: none"> address: <ul style="list-style-type: none"> electronicMailAddress: image2000@jrc.it role pointOfContact
	Implementing instructions	The role of the responsible party serving as a metadata point of contact is out of scope of the INSPIRE Implementing Rules, but this property is mandated by ISO 19115. Its value can be defaulted to pointOfContact . See also SC 15 and SC 16

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:contact>
    <gmd:CI_ResponsibleParty>
      <gmd:organisationName>
        <gco:CharacterString>SDI Unit, Institute for Environment and Sustainability,
Joint Research Centre</gco:CharacterString>
      </gmd:organisationName>
      <gmd:contactInfo>
        <gmd:CI_Contact>
          <gmd:address>
            <gmd:CI_Address>
              <gmd:electronicMailAddress>
                <gco:CharacterString>image2000@jrc.it</gco:CharacterString>
              </gmd:electronicMailAddress>
            </gmd:CI_Address>
          </gmd:address>
        </gmd:CI_Contact>
      </gmd:contactInfo>
      <gmd:role>
        <gmd:CI_RoleCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resou
rces/Codelist/gmxCodetlists.xml#CI_RoleCode"
codeListValue="pointOfContact">pointOfContact</gmd:CI_RoleCode>
        </gmd:role>
      </gmd:CI_ResponsibleParty>
    </gmd:contact>
  </gmd:MD_Metadata ...

```

```

    </gmd:contact>
...
</gmd:MD_Metadata>

```

2.11.2 Metadata date

IR	Reference	Part B 10.2
	Element name	Metadata date
	Obligation/Condition	Mandatory
	Multiplicity	[1]
ISO 19115	Number	9
	Name	dateStamp
	Definition	Date that the metadata was created.
	XPath	dateStamp
	Data type	Date
	Domain	ISO 8601
	Example	2005-03-27
Implementing instructions		None

Example of XML encoding:

```

<gmd:MD_Metadata ...
...
  <gmd:dateStamp>
    <gco:Date>2005-04-18</gco:Date>
  </gmd:dateStamp>
...
</gmd:MD_Metadata>

```

2.11.3 Metadata language

IR	Reference	Part B 10.3
	Element name	Metadata language
	Obligation/Condition	Mandatory
	Multiplicity	[1]
ISO 19115	Number	3
	Name	language
	Definition	Language used for documenting metadata.
	XPath	language
	Data type	LanguageCode (ISO/TS 19139)
	Domain	<p>Codelist (See ISO/TS 19139) based on alpha-3 codes of ISO 639-2. Use only three-letter codes from in ISO 639-2/B (bibliographic codes), as defined at http://www.loc.gov/standards/iso639-2/</p> <p>The list of codes for the 23 official EU languages is:</p> <p>Bulgarian – bul Czech – cze Danish – dan Dutch – dut English – eng Estonian – est Finnish – fin French – fre German – ger Greek – gre Hungarian – hun Irish – gle Italian – ita Latvian – lav Lithuanian – lit Maltese – mlt Polish – pol Portuguese – por Romanian – rum Slovak – slo Slovenian – slv Spanish – spa Swedish – swe</p>
Example	eng	
Implementing instructions	The language property is not mandated by ISO 19115, but is mandated for conformance to the INSPIRE Metadata Implementing rules (See SC1 in 1.2).	

Examples of XML encoding:

Please refer to the examples for Resource Language

3 Detailed mapping

3.1 Introduction

This structure is presented as a set of template instances of ISO 19115 and ISO 19119 classes. The template instance of a class is defined by a set of property instances. The description of each property instance is composed of:

- A + sign starting the description of the property instance;
- The property label as appearing in ISO 19115 and ISO 19119 UML Models;
- A presence requirement expressed with a cardinality statement between square brackets. This cardinality statement expresses the INSPIRE requirements which implies possible differences with the ISO 19115 cardinality;
- A colon;
- The property type name. The property type is implemented as a sub element of the property. This sub element can be an instance of the property type or an instance of one of its derived types. In the latter case, the derived type is either an ISO type or an extension type defined in a profile.
- A property instance statement which describes how the property type is implemented.

Additional information is provided in a Note section, at the bottom of each table.

This hierarchical set of labels acts as an instance Template. This template only shows the properties in the scope of the INSPIRE metadata elements, which encompass the mandatory properties of ISO 19115 and ISO 19119. The other optional properties of ISO 19115 are not described, but can be present in a real instance.

Additional properties defined in a profile of ISO 19115 or ISO 19119 compliant with the INSPIRE metadata elements can be expressed but are not documented here.

3.2 Resource MetadataSet

An INSPIRE Metadata Set is an instance of:

- the class MD_Metadatas (from ISO 19115),
- the class MI_Metadatas (from ISO 19115-2),
- or, an instance of any community specialisation of one of these two classes.

This instance is composed at least of the following property instances:

+ language [1] : LanguageCode.....	Metadata Language (See 2.11.3)
+ hierarchyLevel [1] : MD_ScopeCode	Resource Type (See 2.2.3 and note 2)
+ contact [1..*] : CI_ResponsibleParty	Metadata point of contact (See 2.11.1 and 3.5.2)
+ dateStamp [1] : Date	Metadata date (See 2.11.2)
+ identificationInfo [1] : MD_Identification	See 3.3 and note 3
+ distributionInfo [0..*] : MD_Distribution	
+ transferOptions [0..*] : MD_Format	
+ online [0..*] : CI_Onlineresource	
+ linkage [1]: URL	(See 2.2.4 and Note 1)
+ dataQualityInfo [0..*] : DQ_DataQuality	See 3.4

Notes :

1. The linkage property is not multiple, but there may be many instances of distributionInfo, and for each many instances of transferOptions and for each many instances of online, implying multiple INSPIRE Resource Locator.
2. There may be many instances of hierarchyLevel, but the value of the INSPIRE Resource Type corresponds to the first instance (See SC3 in 1.2).
3. There may be many instances of identificationInfo, but only the first one will be considered (See SC5 in 1.2).

3.3 Identification Section

3.3.1 Sub-elements for spatial dataset and spatial dataset series

If the Resource Type (i.e., the value of metadata set hierarchyLevel) is dataset or series, the data type of identificationInfo instance will be MD_DataIdentification or a subclass of MD_DataIdentification. Its property instances are described hereafter.

+ citation [1] : CI_Citation	
+ title [1] : CharacterString.....	Resource title (See 2.2.1)
+ date [0..*] : CI_Date.....	See note 1
+ date [1] : Date.....	Date of publication (See 2.6.2)
+ dateType [1] : CI_DateTypeCode.....	publication
+ date [0..1] : CI_Date.....	See notes 1 and 2
+ date [1] : Date.....	Date of last revision (See 2.6.3)
+ dateType [1] : CI_DateTypeCode.....	revision
+ date [0..1] : CI_Date.....	See Note 1 and 3
+ date [1] : Date.....	Date of creation (See 2.6.4)
+ dateType [1] : CI_DateTypeCode.....	creation
+ identifier [1..*] : MD_Identifier.....	Unique resource identifier(See 2.2.5 and SC8)
+ code [1] : CharacterString.....	This is the mandatory code of the identifier
+ codeSpace [0..1] : CharacterString.....	This is the optional namespace of the identifier
+ abstract [1] : CharacterString.....	Resource abstract (See 2.2.2)
+ pointOfContact [1..*] : CI_ResponsibleParty.....	Responsible Organization (See 2.10)
+ descriptiveKeywords [1..*] : MD_Keywords	
+ keyword [1..*] : CharacterString.....	Keyword value (See 2.4.1)
+ thesaurusName [0..1] : CI_Citation.....	Originating controlled vocabulary (See 2.4.2)
+ resourceConstraints [1..*] : MD_Constraints.....	Constraints related to access and use (See 2.9 and 3.6).
+ spatialResolution [0..*] : MD_Resolution.....	Spatial resolution (2.7.2) – See Note 4
+ distance [0..1] : Distance.....	This is the ground distance
+ equivalentScale [0..1] : MD_RepresentativeFraction	
+ denominator [1] : Integer.....	This is equivalent scale denominator
+ language [1..*] : LanguageCode.....	Resource language (See 2.2.7, SC9 in 1.2 and Note 5)
+ extent [1] : EX_Extent.....	See Note 6
+ geographicElement [1..*] : EX_GeographicBoundingBox.....	Geographic bounding box (See 2.5.1)
+ westBoundLongitude [1] : Decimal	
+ eastBoundLongitude [1] : Decimal	
+ southBoundLatitude [1] : Decimal	
+ northBoundLatitude [1] : Decimal	
+ temporalElement [0..*] : EX_TemporalExtent.....	See Note 7
+ extent [1] : TM_Primitive.....	Temporal extent (See 2.6.1)
+ topicCategory [1..*] : MD_TopicCategory.....	Topic category (2.3.1)

Notes:

1. There may be many instances of the date property with different date types including **publication**, **revision** or **creation**. The order of these instances is free. If no instance of this property has the **publication**, **revision** or **creation** date type, then the metadata set has to include the description of a temporal extent. For compliance with ISO 19115, there is necessarily one instance of the date property, whatever its date type, even if a temporal extent is provided in the metadata.
2. The only instance of date having the revision date type matching the INSPIRE last revision date is the one having the more recent date.
3. Even if ISO 19115 allows the presence of many dates having a creation date type, it is considered inconsistent to have more than one creation date (See SC7 in 1.2).
4. MD_Resolution is a union data type. Its content is either a distance property or an equivalent scale property. In case of an equivalent scale, the denominator of the equivalent scale is provided.
5. An instance of the language property is mandated by ISO 19115 ; it can be defaulted to the value of the Metadata Language when the dataset or the dataset series does not contain textual information.
6. There may be other instances, but at least one defining the bounding box is required (See SC10 in 1.2). This instance is not necessarily the first instance.
7. There may be different instances of temporalElement defining the temporal extent of the resource. These instances may be in different instances of extent, one of them possibly handling the geographic bounding box.

3.3.2 Sub-elements for service resources

If the Resource Type (i.e., the value of metadata set hierarchyLevel) is **service**, the data type of identificationInfo instance will be SV_ServiceIdentification or a subclass of SV_ServiceIdentification. Its property instances are described hereafter.

+ citation [1] : CI_Citation	
+ title [1] : CharacterString	Resource title (See 2.2.1)
+ date [0..*] : CI_Date	See note 1
+ date [1] : Date	Date of publication (See 2.6.2)
+ dateType [1] : CI_DateTypeCode	publication
+ date [0..1] : CI_Date	See notes 1 and 2
+ date [1] : Date	Date of last revision (See 2.6.3)
+ dateType [1] : CI_DateTypeCode	revision
+ date [0..1] : CI_Date	See Note 1 and 3
+ date [1] : Date	Date of creation (See 2.6.4)
+ dateType [1] : CI_DateTypeCode	creation
+ abstract [1] : CharacterString	Resource abstract (See 2.2.2)
+ pointOfContact [1..*] : CI_ResponsibleParty	Responsible party (See 2.10.1)
+ descriptiveKeywords [1..*] : MD_Keywords	
+ keyword [1..*] : CharacterString	Keyword value (See 2.4.1)
+ thesaurusName [0..1] : CI_Citation	Originating Controlled Vocabulary (See 2.4.2)
+ resourceConstraints [1..*] : MD_Constraints	See 3.6
+ serviceType [1] : GenericName	(See 2.3.2)
+ couplingType [1] : SV_CouplingType	Mandated by ISO 19119. See Note 8
+ containsOperations [1..*] : SV_OperationMetadata	Mandated by ISO 19119
+ operationName [1] : CharacterString	Mandated by ISO 19119. Default value is unknown
+ DCP [1..*] : DCPList	Mandated by ISO 19119. Default value is WebServices
+ connectPoint [1..*] : CI_OnlineResource	Mandated by ISO 19119.
+ linkage [1] : URL	Mandated by ISO 19119. See Note 5
+ extent [1..*] : EX_Extent	See Note 4
+ geographicElement [1..*] : EX_GeographicBoundingBox	Geographic bounding box (See 2.5.1)
+ westBoundLongitude [1] : Decimal	
+ eastBoundLongitude [1] : Decimal	
+ southBoundLatitude [1] : Decimal	
+ northBoundLatitude [1] : Decimal	
+ temporalElement [0..*] : EX_TemporalExtent	See Note 6
+ extent [1] : TM_Primitive	Temporal extent (See 2.6.1)
+ operatesOn [0..*] : MD_DataIdentification	Coupled resource (See 2.2.6 and Note 7)

Notes:

1. There may be many instances of the date property with different date types including **publication**, **revision** or **creation**. The order of these instances is free. If no instance of this property has the **publication**, **revision** or **creation** date type, then the metadata set has to include the description of a temporal extent. For compliance with ISO 19115, there is necessarily one instance of the date property, whatever its date type, even if a temporal extent is provided in the metadata.
2. The only instance of date having the revision date type matching the INSPIRE last revision date is the one having the more recent date.
3. Even if ISO 19115 allows the presence of many dates having a creation date type, it is considered inconsistent to have more than one creation date (See SC7 in 1.2).
4. There may be other instances, but at least one defining the bounding box is required (See SC10 in 1.2). This instance is not necessarily the first instance.
5. One of the value of the INSPIRE Metadata Element "Resource Locator" (See 2.2.4) can be used as a default value
6. There may be different instances of temporalElement defining the temporal extent of the resource. These instances may be in different instances of extent, one of them possibly handling the geographic bounding box.
7. This property has to be implemented by reference (See 2.2.6 and SC11 in 1.2)
8. The value is:
 - a. **loose** if there is no coupled Resource (the operatesOn property of SV_ServiceIdentification is not instantiated);
 - b. **tight** if the service only operates on the Coupled Resources
 - c. **mixed** if the service operates on the Coupled Resources and external dataset and dataset series.

3.4 Data Quality Section

3.4.1 Lineage

This part is applicable only to spatial dataset and spatial dataset series. As defined in 3.2, a metadata set may contain different sets of quality information (i.e. instances of DQ_DataQuality or a subclass of DQ_DataQuality). The reason for this multiplicity is that each set is scoped to the whole or a part of the resource. Each of these sets of quality information may contain a lineage statement. INSPIRE only considers one lineage statement concerning the whole resource, i.e. scoped to the dataset or series without any restrictions on the resource extent.

There shall be a single instance of DQ_DataQuality (or one of its subtypes) scoped to the whole spatial dataset or spatial dataset series. This instance may be one also handling conformity statements (as defined in 2.8), but this is not illustrated in its property instances described below.

```
+ scope [1] : DQ_Scope
+ level [1] : MD_ScopeCode..... series for a spatial dataset series or dataset for a spatial dataset
+ extent [0] : EX_Extent ..... There shall not be any restriction on the resource extent
+ lineage [1] : LI_Lineage
+ statement [1] : CharacterString..... Lineage (See 2.7.1)
```

3.4.2 Conformity

The general mechanism to handle the INSPIRE requirements relative to conformity is described in 2.8.

As defined in 3.2 a metadata set may contain different sets of quality information (i.e. instances of DQ_DataQuality or a subclass of DQ_DataQuality). Each set may contain conformity statements relative to one of the INSPIRE conformance specifications. The following property instances of the sets of quality information are involved, possibly with the property instance expressing a lineage statement as defined in 3.4.1.

```
+ report [0..*] : DQ_Element..... See note 1 and 2
+ measureIdentification[1] : MD_Identifier ..... See note 3
+ result[1] : DQ_ConformanceResult
+ specification [1] : CI_Citation ..... Specification (See 2.8.2)
+ explanation [1] : CharacterString ..... See Note 4
+ pass [1] : Boolean ..... Degree (See 2.8.1)
```

Notes:

1. ISO 19115 only reports the result of the conformance evaluation. There may be no information about the conformity to the INSPIRE Conformance specifications, if the conformance has not been evaluated.
2. DQ_Element is an abstract class. It has to be instantiated through one of its concrete subclasses. The appropriate subclass depends on the quality criteria concerned by the quality measure. DQ_DomainConsistency will be used when the conformance does not involve a more precise quality criterion.
3. This metadata element of ISO 19115 will contain the identifier of the conformity statement. This identifier will be used by the application to differentiate the conformance statement related to INSPIRE from others.
4. ISO 19115 mandates an explanation of the meaning of the conformance for this result. A default explanation such as "See the referenced specification" can be used.

3.5 Responsible Organisation

3.5.1 Resource responsible organisation

Each instance of CI_ResponsibleParty or one of its subclasses (see 3.3.2 for services and 3.3.1 for spatial datasets and spatial dataset series) describes a responsible organisation, i.e.:

- The name of the responsible party;
- A contact e-mail address of the responsible party;
- The responsible party role.

Here are the minimum property instances of CI_ResponsibleParty or one of its subclasses expected by INSPIRE:

```
+ organisationName[1] : CharacterString..... The name of the Responsible party (See 2.10.1)
+ contactInfo[1] : CI_Contact
+ address[1..*] : CI_Address..... There may be more than one address, so more than one e-mail
  + electronicEmailAddress [1..*] : CharacterString.... At least one e-mail address of the Responsible party (See 2.10.1)
+ role[1] : CI_RoleCode ..... Responsible party role (See 2.10.2)
```

3.5.2 Metadata point of contact

The metadata points of contact are also described by instances of MD_ResponsibleParty:

```
+ organisationName[1] : CharacterString.....The name of the Metadata point of contact (See 2.11.1)
+ contactInfo[1] : CI_Contact
+ address[1..*] : CI_Address.....There may be more than one address, so more than one e-mail
  + electronicEmailAddress [1..*] : CharacterStringAt least one e-mail address of the Metadata point of contact (See 2.11.1)
+ role[1] : CI_RoleCode .....See Note 1
```

Notes:

1. ISO 19115 mandates the definition of the role of the responsible party. The default role is pointOfContact, but a more appropriate choice is encouraged.

3.6 Constraint section

Depending on the effective instance of MD_Constraints⁸, the following properties may have to be considered:

```
+useLimitation [0..*] : CharacterString ..... Conditions applying to access and use (See 2.9.2)
+accessConstraints [0..*] : MD_RestrictionCode..... Limitations on public access (See 2.9.1) –See Note 1
+otherConstraints [0..*] : CharacterString ..... Limitations on public access (See 2.9.1) –See Note 1
+classification [0..1] : MD_ClassificationCode ..... Limitations on public access (See 2.9.1) –See Note 2
```

Notes:

1. If the value of accessConstraints is otherRestrictions, then the instances of otherConstraints also describe Limitations on public access (See 2.9.1), but the special value otherConstraints has not to be reported as a Limitations on public access.
2. If the value of classification is not unclassified, the classification has to be reported as a Limitation on Public Access.

⁸ accessConstraints and otherConstraints are specific to instances of MD_LegalConstraints or one of its subclasses. classification is specific to instances of MD_SecurityConstraints and one of its subclasses.

3.7 Abbreviations

CEN	C omité E uropéen de N ormalisation
CSW	OGC C atalog S ervice W eb
EN	E uropean N orm by CEN
EU	E uropean U nion
GML	G eography M arkup L anguage
IRs	I mplementing R ules
ISO	I nternational O rganisation for S tandardization
ISO/TS	ISO Technical Specification
OGC	O pen G eospatial C onsortium
UML	U nified M odelling L anguage
URL	U niform R esource L ocator
XML	e Xtensible M arkup L anguage

Annex A – ISO/TS 19139 encoding of the INSPIRE metadata elements

A.1 Introduction

This annex defines the XML ISO/TS 19139 encoding of the INSPIRE metadata elements. This XML encoding is based on XML Schemas derived from the UML models of ISO 19115 and ISO 19119 using the encoding rules defined in ISO/TS 19139 and:

- the XML Schema Implementation of ISO 19115 and the related standards defined in ISO/TS 19139;
- the XML Schema implementation of ISO 19119 defined in CSW2 AP ISO.

The XML encoding of the INSPIRE metadata elements shall follow the instance template defined in Section 3 and the instructions of Section 2 of this document with respect to the following instructions.

A.2 From the conceptual schema to XML File instances

The way in which the geographic metadata XML Schema is expected to be used makes it necessary to keep the organisation of the data, its associated metadata and the related information in very flexible files. Since the MD_Metadata XML element will rarely be the root element of an XML File, depending on the context, it may appear one or many times in a single XML File describing one or many different types of resources.

A.3 Polymorphism

It is possible to have an XML file containing a metadata set without containing a single MD_Metadata XML element. This is a consequence of polymorphism, which may imply that an XML element representing a subclass of MD_Metadata, potentially defined in a user community profile, occurs instead of the MD_Metadata XML element. This is true for MD_Metadata as well as for any of the concepts defined in the ISO 19100 series of International Standards.

A.4 Management of polymorphism

A.4.1 Management of community extensions

A.3 of ISO 19139 has a specific requirement to aid the understanding of user profiled metadata sets. The XML element of any new metadata element has to support a mandatory XML attribute called isoType that is expected to contain the name of the ISO class it derives from directly or indirectly.

```
<MY_Metadata gco:isotype="MD_Metadata">
  <!-- Standard properties not detailed here -->
  <myProperty>
    <gco:CharacterString>Whatever text</gco:CharacterString>
  </myProperty>
</MY_Metadata>
```

A.4.2 Parsing of metadata files

To accommodate polymorphism of the data types, parsing of metadata files has to be driven by the XML elements corresponding to the properties of the UML models (look rather for the metadata elements named identificationInfo, than the metadata elements named MD_DataIdentification or SV_ServiceIdentification). The elements corresponding to the data type can generally be skipped.

When it is necessary to evaluate the XML element representing data types (e.g., because the application needs to consider the data identification info, but not the service identification info), it is important to look for the XML element corresponding to the expected ISO data type (e.g., gco:MD_DataIdentification) or the XML element for which the value of gco:isotype is the expected data type (e.g. MD_DataIdentification). There is no namespace indication in the value of the isoType attribute.

A.5 Management of containment by reference

Any instance of a UML property can be implemented:

- by value, i.e. the instance of its datatype is a subelement of the property instance;

```
<gmx:MX_Aggregate>
  <gmd:composedOf>
    <gmx:MX_Dataset>
      ...
    </gmx:MX_Dataset>
  </gmd:composedOf>
  <gmd:seriesMetadata> ... </gmd:seriesMetadata>
</gmx:MX_Aggregate>
```

- by reference, i.e. the property instance handles a xlink:href attribute which value is a reference (typically URL) to the instance of its datatype. In this case, the instance of the datatype handles an id XML attribute serving as an identifier.


```
<gmx: MX_Aggregate>
  <gmd:composedOf xlink:href="product1.xml">
    <gmd:seriesMetadata> ... </gmd:seriesMetadata>
  </gmx:MX_Aggregate>
```

The use of containment by reference is of course a very good way to ensure the consistency of the XML data and to reduce the maintenance cost. However it complicates the parsing of the XML file. It is recommended that the parser use a generic mechanism to manage the containment by-reference.

A.6 ISO 19139 and multilingual metadata

An optional but repeatable attribute "locale" has been added to the class MD_Metadata. Two cases are to be considered:

- When this attribute is not implemented, the metadata set is expected to be monolingual: the language of the metadata is defined by the language attribute of MD_Metadata.
- When this attribute is implemented, each instance represents a locale (language, country and character encoding) in which the metadata elements may be translated. The language attribute still defines the default language of the metadata, i.e. the language in which all the metadata elements are expressed. Then each metadata element can be translated in some of the locales define for the metadata set.




The metadata elements which may require translations are those of type CharacterString having a free text domain.

	Name / Role name	Short Name	Definition	Obligation / Condition	Maximum occurrence	Data type	Domain
1	MD_Metadata	Metadata	root entity which defines metadata about a resource or resources	M	1	Class	Lines 2-22
2	fileIdentifier	mdFileID	unique identifier for this metadata file	O	1	CharacterString	Free text

Data type	Domain
Class	Lines 2-22
CharacterString	Free text

Support of free text is enabled via a subtype of CharacterString called PT_FreeText which aggregates a set of localised character strings through its textGroup property. Each localised character string provides a translation of the character string in the related locale.



The following clauses define the way multilingual metadata are implemented.

A.6.1 The default language

The default language of a metadata set is defined by the language property of MD_Metadata while the characterSet property defines the corresponding character encoding. Here is a sample instance of the class MD_Metadata illustrating the use of both properties.

```

<MD_Metadata>
  <!-- portions of metadata not shown -->
  <language>

```

```

    <LanguageCode
      codeList="resources/Codelist/gmxcodelists.xml#LanguageCode"
      codeListValue="eng"> English </LanguageCode>
  </language>
  <characterSet>
    <MD_CharacterSetCode
      codeList="resources/Codelist/gmxcodelists.xml#MD_CharacterSetCode"
      codeListValue="utf8"> UTF-8 </MD_CharacterSetCode>
    </characterSet>
    <!-- portions of metadata not shown -->
  </MD_Metadata>

```

A.6.2 Alternate languages

Each metadata alternate language of the metadata is defined through the locale property of MD_Metadata. In the following example, some of these metadata are translated into French:

```

<MD_Metadata>
  <!-- portions of metadata not shown, particularly the language and
  characterSet properties which are not detailed -->
  <locale>
    <PT_Locale id="locale-fr">
      <languageCode>
        <LanguageCode
          codeList="resources/Codelist/gmxcodelists.xml#
LanguageCode"
          codeListValue="fra"> French </LanguageCode>
        </languageCode>
      <characterEncoding>
        <MD_CharacterSetCode
          codeList="resources/Codelist/gmxcodelists.xml#
MD_CharacterSetCode"
          codeListValue="utf8">UTF 8</MD_CharacterSetCode>
        </characterEncoding>
      </PT_Locale>
    </locale>
    <!-- portions of metadata not shown -->
  </MD_Metadata>

```

A.6.3 Embedded translations

Any metadata element having a free text domain (e.g. the abstract property of MD_DataIdentification) can then be instantiated like this:

```

<abstract xsi:type="PT_FreeText_PropertyType">
  <gco:CharacterString>Brief narrative summary of the content of the
  resource</gco:CharacterString>
  <!--== Alternative value ==-->
  <PT_FreeText>
    <textGroup>
      <LocalisedCharacterString locale="#locale-fr">Résumé succinct
  du contenu de la ressource</LocalisedCharacterString>
    </textGroup>
  </PT_FreeText>
</abstract>

```

The xsi:type attribute indicates that this instance of the abstract property is not instantiated through a simple CharacterString, but rather as a free text. As a consequence, the element

contains a complementary `PT_FreeText` subelement containing one or more `textGroup` elements (one per translation).

A.6.4 Use of translation files

In the preceding example, the definition of the locale property is provided by value which implies that the translations are embedded with default language metadata. It is also possible to store the translations corresponding to a given language into a translation file using the **PT_LocaleContainer** class. In such case, it is easier to define the locale within the translation file (e.g. `fr-fr.xml`) and to express the instance of the `MD_Metadata` locale property by reference.

```
<gmd:locale xlink:href="./fr-fr.xml#locale-fr"/>
```

The content of the `fr-fr.xml` file would look like this:

```
<PT_LocaleContainer>
  <!-- portions of metadata not shown -->
  <locale>
    <PT_Locale id="locale-fr">
      <languageCode>
        <LanguageCode
          codeList="resources/Codelist/gmxcodelists.xml#
LanguageCode"
          codeListValue="fra"> French </LanguageCode>
        </languageCode>
      <characterEncoding>
        <MD_CharacterSetCode
          codeList="../Codelist/ML_gmxCodelists.xml#
MD_CharacterSetCode"
          codeListValue="utf8">UTF 8</MD_CharacterSetCode>
        </characterEncoding>
      </PT_Locale>
    </locale>
    <!-- portions of metadata not shown -->
    <localisedString>
      <LocalisedCharacterString locale="#locale-fr" id="#abstract-
fr"> Résumé succinct du contenu de la
ressource</LocalisedCharacterString>
    </localisedString>
    <!-- portions of metadata not shown -->
  </PT_LocaleContainer>
```

The multilingual instance of the abstract property now implements the translation by reference to the translation file:

```
<abstract xsi:type="PT_FreeText_PropertyType">
  <gco:CharacterString>Brief narrative summary of the content of the
resource</gco:CharacterString>
  <!--== Alternative value ==-->
  <PT_FreeText>
    <textGroup xlink:href="fr-fr.xml#abstract-fr"/>
  </PT_FreeText>
</abstract>
```

A.7 Contexts of use

A.7.1 Use of ISO 19139 in the context of a Catalogue Service

When the data being passed through a cataloguing service is XML encoded, the catalogue service interface defines the different XML Schemas to be used as a response to the user queries. When the geographic metadata XML Schema is used, there should be one or many MD_Metadata instances in the returned XML File.

A.7.2 Use of ISO 19139 in the context of the standard interchange by transfer

The transfer aggregate and transfer dataset concepts are the two major components of an interchange by transfer. There may be one or many XML Files composing the interchange, but the root element of at least one of the files is an XML instance of MX_Dataset, MX_Aggregate or one of their extensions. From such an element, the parsing of the interchange is model driven and it follows the principles described in 7.4 of ISO 19139. See ISO 19139 for details about MX_Dataset and MX_Aggregate.

A.8 Character encoding

Character encoding is defined in MD_Metadata.characterEncoding and MD_Metadata.locale. Preferably this should be UTF-8 if the XML files contain multilingual metadata.

A.9 Temporal extent encoding

In ISO 19115, temporal extents are of type TM_Primitive (abstract type from ISO 19108). In ISO 19139, this type (and its sub-types) are mapped to ISO 19136 temporal types and W3C built-in types. In the INSPIRE Metadata Element Set for discovery, the concrete TM_Period subtype of TM_Primitive is used as type for the XML element temporalExtent. It is implemented as type TimePeriod from ISO 19136.

TimePeriod offers three options to express a time interval:

- Use two TimePosition elements for beginPosition and endPosition. Date and time information is contained in-line and cannot be referenced from another XML Element. Only the TimePeriod element can, through its gml:id.

```
<?xml version="1 0" encoding="UTF-8"?>
<gmd:MD_Metadata>
<!-- Portions of metadata not shown -->
<gmd:extent>
  <gmd:EX_Extent>
    <gmd:temporalElement>
      <gmd:EX_TemporalExtent>
        <gmd:extent>
          <gml:TimePeriod gml:id="extent">
            <gml:beginPosition>1977-03-
10T11:45:30</gml:beginPosition>
            <gml:endPosition>2005-01-
15T09:10:00</gml:endPosition>
          </gml:TimePeriod>
        </gmd:extent>
      </gmd:EX_TemporalExtent>
    </gmd:temporalElement>
  </gmd:EX_Extent>
</gmd:extent>
<!-- Portions of metadata not shown -->
</gmd:MD_Metadata>
```

- Use two TimeInstant elements: Date and time information is here contained by reference and the TimeInstant elements can be re-used through a reference from another XML element in the XML file. The TimePeriod element can also be re-used.

```
<?xml version="1.0" encoding="UTF-8"?>
<gmd:MD_Metadata>
<!-- Portions of metadata not shown -->
<gmd:extent>
  <gmd:EX_Extent>
    <gmd:temporalElement>
      .....<gmd:EX_TemporalExtent>
      .....<gmd:extent>
      .....<gml:TimePeriod gml:id="extent">
      .....<gml:begin>
      .....<gml:TimeInstant gml:id="t11">
          <gml:timePosition>1977-03-
            10T11:45:30</gml:timePosition>
      .....</gml:TimeInstant>
      .....</gml:begin>
      .....<gml:end>
      .....<gml:TimeInstant gml:id="t12">
          <gml:timePosition>2005-01-
            15T09:10:00</gml:timePosition>
      .....</gml:TimeInstant>
      .....</gml:end>
      .....</gml:TimePeriod>
      .....</gmd:extent>
      .....</gmd:EX_TemporalExtent>
      .....</gmd:temporalElement>
      ...</gmd:EX_Extent>
    </gmd:extent>
<!-- Portions of metadata not shown -->
</gmd:MD_Metadata>
```

- The two previous methods can be used in combination: one TimePeriod limit can be expressed as a TimePosition and the other as a TimeInstant:

```
<?xml version="1 0" encoding="UTF-8"?>
<gmd:MD_Metadata>
<!-- Portions of metadata not shown -->
<gmd:extent>
  <gmd:EX_Extent>
    <gmd:temporalElement>
      <gmd:EX_TemporalExtent>
        <gmd:extent>
          <gml:TimePeriod gml:id="extent">
            <gml:begin>
              <gml:TimeInstant gml:id="t11">
                <gml:timePosition>1977-03-
                  10T11:45:30</gml:timePosition>
              </gml:TimeInstant>
            </gml:begin>
              <gml:endPosition>2005-01-
                15T09:10:00</gml:endPosition>
            </gml:TimePeriod>
          </gmd:extent>
        </gmd:EX_TemporalExtent>
      </gmd:temporalElement>
    </gmd:EX_Extent>
  </gmd:extent>
<!-- Portions of metadata not shown -->
</gmd:MD_Metadata>
```

A.10 Spatial resolution encoding

The spatial resolution of a dataset or dataset series can be expressed as an equivalent scale or as a resolution distance:

- Expression as an equivalent scale:

```
<?xml version="1.0" encoding="UTF-8"?>
<gmd:MD_Metadata>
<!-- Portions of metadata not shown -->
<gmd:identificationInfo>
<!-- Portions of metadata not shown -->
<gmd:spatialResolution>
  <gmd:MD_Resolution>
    <gmd:equivalentScale>
      <gmd:MD_RepresentativeFraction>
        <gmd:denominator>
          <gco:Integer>25000</gco:Integer>
        </gmd:denominator>
      </gmd:MD_RepresentativeFraction>
    </gmd:equivalentScale>
  </gmd:MD_Resolution>
</gmd:spatialResolution>
<!-- Portions of metadata not shown -->
</gmd:identificationInfo>
<!-- Portions of metadata not shown -->
</gmd:MD_Metadata>
```

In this case, the spatial resolution is expressed as the denominator of the scale of a comparable hardcopy map or chart.

- Expression as a resolution distance:

```
<?xml version="1.0" encoding="UTF-8"?>
<gmd:MD_Metadata>
<!-- Portions of metadata not shown -->
<gmd:identificationInfo>
<!-- Portions of metadata not shown -->
<gmd:spatialResolution>
  <gmd:MD_Resolution>
    <gmd:distance>
      .....<gco:Distance uom="#cm">25</gco:Distance>
    </gmd:distance>
  </gmd:MD_Resolution>
</gmd:spatialResolution>
<!-- Portions of metadata not shown -->
</gmd:identificationInfo>
<!-- Portions of metadata not shown -->
</gmd:MD_Metadata>
```

In this case, the spatial resolution is expressed as the ground sample distance, implemented through the gco:Distance type. The unit of measure is either a conventional unit of measure symbol or a link to a definition. The latter case is illustrated above.

- If needed, the two options can be used in conjunction:

```

<?xml version="1 0" encoding="UTF-8"?>
<gmd:MD_Metadata>
<!-- Portions of metadata not shown -->
<gmd:identificationInfo>
<!-- Portions of metadata not shown -->
<gmd:spatialResolution>
  <gmd:MD_Resolution>
    <gmd:distance>
      <gco:Distance uom="#cm">25</gco:Distance>
    </gmd:distance>
  </gmd:MD_Resolution>
</gmd:spatialResolution>
<gmd:spatialResolution>
  <gmd:MD_Resolution>
    <gmd:equivalentScale>
      <gmd:MD_RepresentativeFraction>
        <gmd:denominator>
          <gco:Integer>25000</gco:Integer>
        </gmd:denominator>
      </gmd:MD_RepresentativeFraction>
    </gmd:equivalentScale>
  </gmd:MD_Resolution>
</gmd:spatialResolution>
<!-- Portions of metadata not shown -->
</gmd:identificationInfo>
<!-- Portions of metadata not shown -->
</gmd:MD_Metadata>

```

N.B. In this case, the property spatialResolution needs to be instantiated twice.

A.11 Codelists

The two recommended ways to reference codelists are those expressed in the examples shown in 2.7.2 Resource Language.

A.12 Example of ISO 19139 XML Metadata Sets

A.12.1 Dataset

A.12.1.1 INSPIRE view

- + **Part B 1 Identification:**
 - + **Part B 1.1 Resource Title:** Image2000 Product 1 (nl2) Multispectral
 - + **Part B 1.2 Resource Abstract:** IMAGE2000 product 1 individual orthorectified scenes. IMAGE2000 was produced from ETM+ Landsat 7 satellite data and provides, etc. etc...
 - + **Part B 1.3 Resource Type:** dataset
 - + **Part B 1.4 Resource Locator:** <http://image2000.jrc.it>
 - + **Part B 1.5 Resource Unique Identifier:**
 - + **code:** image2000_1_nl2_multi
 - + **codeSpace:** <http://image2000.jrc.it>
 - + **Part B 1.7 Resource language:** eng
- + **Part B 2 Classification of data and services:**
 - + **Part B 2.1 Topic category:** imageryBaseMapsEarthCover
- + **Part B 3 Keyword:**
 - + **Part B 3.1 Keyword value:** Land cover
 - + **Part B 3.2 Originating Controlled Vocabulary:**
 - + **title:** GEMET Thesaurus version 1.0
 - + **reference date:**
 - + **date:** 2001-01-01
 - + **date type:** publication
- + **Part B 4 Geographic Location:**
 - + **Part B 4.1 Bounding Box:**
 - + **West:** +3.93
 - + **East:** +7.57
 - + **North:** +52.10
 - + **South:** +54.10
- + **Part B 5 Temporal Reference:**
 - + **Part B 5.2 Date of publication:** 2000-01-01
- + **Part B 6 Quality and validity:**
 - + **Part B 6.1 Lineage:** Product 1 scenes correspond to the path/row of the Landsat orbit. All Image2000 product 1 scenes are ortho-corrected, etc. etc..
 - + **Part B 6.2 Spatial Resolution:** 25.0
 - + **Part B 7.1 Specification:**
 - + **title:** INSPIRE Implementing rules laying down technical arrangements for the interoperability and harmonisation of orthoimagery
 - + **publication date:** 2011-05-15
 - + **Part B 7.2 Degree:** true
- + **Part B 8 Constraints related to access and use:**
 - + **Part B 8.2 Limitation on public access:** no limitations
- + **Part B 8 Constraints related to access and use:**
 - + **Part B 8.1 Condition applying to access and use:** no conditions apply
- + **Part B 9 Responsible Organisation:**
 - + **Part B 9.1 Responsible party:**
 - + **organisation:** Joint Research Centre
 - + **e-mail:** image2000@jrc.it

- + **Part B 9.2 Responsible party role:** custodian
- + **Part B 10 Metadata on metadata:**
 - + **Part B 10.1 Metadata point of contact:**
 - + **organisation:** Joint Research Centre
 - + **e-mail:** image2000@jrc.it
 - + **Part B 10.2 Metadata date:** 2005-04-18
 - + **Part B 10.3 Metadata language:** eng

A.12.1.2 ISO/TS 19139 XML File

NOTE: This file is an ISO compliant metadata record extracted from the INSPIRE geo-portal. It may contain more elements than the minimum required to comply with the INSPIRE metadata Regulation.

```
<?xml version="1.0" encoding="UTF-8"?>
<gmd:MD_Metadata xsi:schemaLocation="http://www.isotc211.org/2005/gmd
http://schemas.opengis.net/iso/19139/20060504/gmd/gmd.xsd" xmlns:gmd="http://www.isotc211.org/2005/gmd"
xmlns:gco="http://www.isotc211.org/2005/gco" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:gml="http://www.opengis.net/gml">
  <gmd:fileIdentifier>
    <gco:CharacterString>029097fd-2ef2-487c-a5ca-6ec7a3dbac53</gco:CharacterString>
  </gmd:fileIdentifier>
  <gmd:language>
    <gmd:LanguageCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#LanguageCode" codeListValue="eng">eng</gmd:LanguageCode>
  </gmd:language>
  <gmd:hierarchyLevel>
    <gmd:MD_ScopeCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#MD_ScopeCode" codeListValue="dataset">dataset</gmd:MD_ScopeCode>
  </gmd:hierarchyLevel>
  <gmd:contact>
    <gmd:CI_ResponsibleParty>
      <gmd:organisationName>
        <gco:CharacterString>SDI Unit, Institute for Environment & Sustainability, Joint Research
Centre</gco:CharacterString>
      </gmd:organisationName>
      <gmd:contactInfo>
        <gmd:CI_Contact>
          <gmd:address>
            <gmd:CI_Address>
              <gmd:electronicMailAddress>
                <gco:CharacterString>image2000@jrc.it</gco:CharacterString>
              </gmd:electronicMailAddress>
            </gmd:CI_Address>
          </gmd:address>
        </gmd:CI_Contact>
      </gmd:contactInfo>
      <gmd:role>
        <gmd:CI_RoleCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#CI_RoleCode" codeListValue="pointOfContact">pointOfContact</gmd:CI_RoleCode>
      </gmd:role>
    </gmd:CI_ResponsibleParty>
  </gmd:contact>
  <gmd:dateStamp>
    <gco:Date>2005-04-18</gco:Date>
  </gmd:dateStamp>
  <gmd:metadataStandardName>
    <gco:CharacterString>ISO19115</gco:CharacterString>
  </gmd:metadataStandardName>
  <gmd:metadataStandardVersion>
    <gco:CharacterString>2003/Cor. 1:2006</gco:CharacterString>
  </gmd:metadataStandardVersion>
  <gmd:identificationInfo>
    <gmd:MD_DataIdentification id="image2000_1_nl2_multi">
      <gmd:citation>
        <gmd:CI_Citation>
          <gmd:title>
            <gco:CharacterString>Image2000 Product 1 (nl2) Multispectral</gco:CharacterString>
          </gmd:title>
          <gmd:date>
            <gmd:CI_Date>
              <gmd:date>
                <gco:Date>2007-09-15</gco:Date>
              </gmd:date>
            </gmd:CI_Date>
          </gmd:dateType>
            <gmd:CI_DateTypeCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#CI_DateTypeCode" codeListValue="creation">creation</gmd:CI_DateTypeCode>
          </gmd:dateType>
        </gmd:CI_Citation>
      </gmd:citation>
    </gmd:MD_DataIdentification>
  </gmd:identificationInfo>

```

```

    </gmd:date>
    <gmd:date>
      <gmd:CI_Date>
        <gmd:date>
          <gco:DateTime>2007-11-15T11:15:00</gco:DateTime>
        </gmd:date>
        <gmd:dateType>
          <gmd:CI_DateTypeCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#CI_DateTypeCode" codeListValue="revision">revision</gmd:CI_DateTypeCode>
          </gmd:dateType>
        </gmd:CI_Date>
      </gmd:date>
    </gmd:date>
    <gmd:CI_Date>
      <gmd:date>
        <gco>Date>2007-09-15</gco>Date>
      </gmd:date>
      <gmd:dateType>
        <gmd:CI_DateTypeCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#CI_DateTypeCode" codeListValue="publication">publication</gmd:CI_DateTypeCode>
        </gmd:dateType>
      </gmd:CI_Date>
    </gmd:date>
    <gmd:identifier>
      <gmd:RS_Identifier>
        <gmd:code>
          <gco:CharacterString>image2000_1_n12_multi</gco:CharacterString>
        </gmd:code>
        <gmd:codeSpace>
          <gco:CharacterString>http://image2000.jrc.it</gco:CharacterString>
        </gmd:codeSpace>
      </gmd:RS_Identifier>
    </gmd:identifier>
  </gmd:CI_Citation>
</gmd:citation>
<gmd:abstract>
  <gco:CharacterString>IMAGE2000 product 1 individual orthorectified scenes. IMAGE2000 was
produced from ETM+ Landsat 7 satellite data and provides a consistent European coverage of individual
orthorectified scenes in national map projection systems. The year 2000 was targeted as reference year, but a
deviation of maximum 1-year was allowed to obtain a full coverage of Europe, which involves approximately 450
Landsat TM Frames. Where Landsat 7 data were not available, Landsat 5 data have been used instead. The spatial
resolution is 25 metres for multispectral and 12.5 metres for panchromatic imagery. </gco:CharacterString>
</gmd:abstract>
<gmd:pointOfContact>
  <gmd:CI_ResponsibleParty>
    <gmd:organisationName>
      <gco:CharacterString>SDI Unit, Institute for Environment and Sustainability, Joint Research
Centre</gco:CharacterString>
    </gmd:organisationName>
    <gmd:contactInfo>
      <gmd:CI_Contact>
        <gmd:address>
          <gmd:CI_Address>
            <gmd:electronicMailAddress>
              <gco:CharacterString>image2000@jrc.it</gco:CharacterString>
            </gmd:electronicMailAddress>
          </gmd:CI_Address>
        </gmd:address>
      </gmd:CI_Contact>
    </gmd:contactInfo>
    <gmd:role>
      <gmd:CI_RoleCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#CI_RoleCode" codeListValue="custodian">custodian</gmd:CI_RoleCode>
    </gmd:role>
  </gmd:CI_ResponsibleParty>
</gmd:pointOfContact>
<gmd:descriptiveKeywords>
  <gmd:MD_Keywords>
    <gmd:keyword>
      <gco:CharacterString>Land cover</gco:CharacterString>
    </gmd:keyword>
    <gmd:thesaurusName>
      <gmd:CI_Citation>
        <gmd:title>
          <gco:CharacterString>GEMET - INSPIRE themes, version
1.0</gco:CharacterString>

```

```

        </gmd:title>
        <gmd:date>
          <gmd:CI_Date>
            <gmd:date>
              <gco:Date>2008-06-01</gco:Date>
            </gmd:date>
            <gmd:dateType>
              <gmd:CI_DateTypeCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#CI_DateTypeCode" codeListValue="publication">publication</gmd:CI_DateTypeCode>
              </gmd:dateType>
            </gmd:CI_Date>
          </gmd:date>
        </gmd:CI_Citation>
        </gmd:thesaurusName>
        </gmd:MD_Keywords>
      </gmd:descriptiveKeywords>
      <gmd:resourceConstraints>
        <gmd:MD_Constraints>
          <gmd:useLimitation>
            <gco:CharacterString>no conditions apply</gco:CharacterString>
          </gmd:useLimitation>
        </gmd:MD_Constraints>
      </gmd:resourceConstraints>
      <gmd:resourceConstraints>
        <gmd:MD_LegalConstraints>
          <gmd:accessConstraints>
            <gmd:MD_RestrictionCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#MD_RestrictionCode"
codeListValue="otherRestrictions">otherRestrictions</gmd:MD_RestrictionCode>
          </gmd:accessConstraints>
          <gmd:otherConstraints>
            <gco:CharacterString>no limitations</gco:CharacterString>
          </gmd:otherConstraints>
        </gmd:MD_LegalConstraints>
      </gmd:resourceConstraints>
      <gmd:spatialResolution>
        <gmd:MD_Resolution>
          <gmd:distance>
            <gco:Distance
uom="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/uom/ML_gmxUom.xml
#m">25.0</gco:Distance>
          </gmd:distance>
        </gmd:MD_Resolution>
      </gmd:spatialResolution>
      <gmd:spatialResolution>
        <gmd:MD_Resolution>
          <gmd:equivalentScale>
            <gmd:MD_RepresentativeFraction>
              <gmd:denominator>
                <gco:Integer>50000</gco:Integer>
              </gmd:denominator>
            </gmd:MD_RepresentativeFraction>
          </gmd:equivalentScale>
        </gmd:MD_Resolution>
      </gmd:spatialResolution>
      <gmd:language>
        <gmd:LanguageCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#LanguageCode" codeListValue="eng">eng</gmd:LanguageCode>
        </gmd:language>
      <gmd:topicCategory>
        <gmd:MD_TopicCategoryCode>imageryBaseMapsEarthCover</gmd:MD_TopicCategoryCode>
      </gmd:topicCategory>
      <gmd:extent>
        <gmd:EX_Extent>
          <gmd:geographicElement>
            <gmd:EX_GeographicBoundingBox>
              <gmd:westBoundLongitude>
                <gco:Decimal>3.93</gco:Decimal>
              </gmd:westBoundLongitude>
              <gmd:eastBoundLongitude>
                <gco:Decimal>7.57</gco:Decimal>
              </gmd:eastBoundLongitude>
              <gmd:southBoundLatitude>
                <gco:Decimal>52.10</gco:Decimal>
              </gmd:southBoundLatitude>
              <gmd:northBoundLatitude>

```

```

        <gco:Decimal>54.10</gco:Decimal>
      </gmd:northBoundLatitude>
    </gmd:EX_GeographicBoundingBox>
  </gmd:geographicElement>
</gmd:EX_Extent>
</gmd:extent>
<gmd:extent>
  <gmd:EX_Extent>
    <gmd:temporalElement>
      <gmd:EX_TemporalExtent>
        <gmd:extent>
          <gml:TimePeriod gml:id="IDf329b5fa-4ca4-4c8e-ad0f-27e399386ab2">
            <gml:beginPosition>1977-03-10T11:45:30</gml:beginPosition>
            <gml:endPosition>2005-01-15T09:10:00</gml:endPosition>
          </gml:TimePeriod>
        </gmd:extent>
      </gmd:EX_TemporalExtent>
    </gmd:temporalElement>
  </gmd:EX_Extent>
</gmd:extent>
</gmd:MD_DataIdentification>
</gmd:identificationInfo>
<gmd:distributionInfo>
  <gmd:MD_Distribution>
    <gmd:distributionFormat>
      <gmd:MD_Format>
        <gmd:name gco:nilReason="inapplicable"/>
        <gmd:version gco:nilReason="inapplicable"/>
      </gmd:MD_Format>
    </gmd:distributionFormat>
    <gmd:transferOptions>
      <gmd:MD_DigitalTransferOptions>
        <gmd:onLine>
          <gmd:CI_OnlineResource>
            <gmd:linkage>
              <gmd:URL>http://image2000.jrc.it/</gmd:URL>
            </gmd:linkage>
          </gmd:CI_OnlineResource>
        </gmd:onLine>
      </gmd:MD_DigitalTransferOptions>
    </gmd:transferOptions>
  </gmd:MD_Distribution>
</gmd:distributionInfo>
<gmd:dataQualityInfo>
  <gmd:DQ_DataQuality>
    <gmd:scope>
      <gmd:DQ_Scope>
        <gmd:level>
          <gmd:MD_ScopeCode codeListValue="dataset"
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#MD_ScopeCode">dataset</gmd:MD_ScopeCode>
        </gmd:level>
      </gmd:DQ_Scope>
    </gmd:scope>
    <gmd:report>
      <gmd:DQ_DomainConsistency>
        <gmd:result>
          <gmd:DQ_ConformanceResult >
            <gmd:specification>
              <gmd:CI_Citation>
                <gmd:title>
                  <gco:CharacterString>INSPIRE Implementing rules laying down technical
arrangements for the interoperability and harmonisation of orthoimagery</gco:CharacterString>
                </gmd:title>
                <gmd:date>
                  <gmd:CI_Date>
                    <gmd:date>
                      <gco:Date>2011-05-15</gco:Date>
                    </gmd:date>
                    <gmd:dateType>
                      <gmd:CI_DateTypeCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#CI_DateTypeCode" codeListValue="publication">publication</gmd:CI_DateTypeCode>
                    </gmd:dateType>
                  </gmd:CI_Date>
                </gmd:date>
              </gmd:CI_Citation>
            </gmd:specification>
          </gmd:DQ_ConformanceResult>
        </gmd:result>
      </gmd:DQ_DomainConsistency>
    </gmd:report>
  </gmd:DQ_DataQuality>
</gmd:dataQualityInfo>
</gmd:MD_DataIdentification>
</gmd:MD_Metadata>
</gmd:MD_Metadata>

```

```

    <gco:CharacterString>See the referenced specification</gco:CharacterString>
  </gmd:explanation>
  <gmd:pass>
    <gco:Boolean>true</gco:Boolean>
  </gmd:pass>
  </gmd:DQ_ConformanceResult>
</gmd:result>
</gmd:DQ_DomainConsistency>
</gmd:report>
<gmd:lineage>
  <gmd:LI_Lineage>
    <gmd:statement>
      <gco:CharacterString>Product 1 scenes correspond to the path/row of the Landsat orbit. All
Image2000 product 1 scenes are ortho-corrected. The ortho-correction method consisted of using a physical model
of the satellite's flight during the scene acquisition, which was then complemented with Ground Control Points
(GCP's) and a Digital Elevation Model (DEM). Map projection information is attached to the model. The resulting
product has excellent accuracy between the spectral bands, sub-pixel location accuracy throughout the image and
excellent preservation of radiometric characteristics. The geometric correction was done on a Country basis -
according to the relevant national map projection system(s). A rigorous orbital model was used. Control point
measurements were used in a weighted least squares adjustment to estimate optimal values for the orbital and
attitude parameters. The adjusted parameters were used to resample the raw scene by cubic convolution in a single
step, instead of the usual two step procedure of first producing a system-corrected scene and then resampling a
second time, thus causing unnecessary smoothing of the data. The final pixel size after resampling is 12.5m for the
panchromatic band, 25m for the multispectral bands and 60m for the thermal band. All the orthorectified scenes are
well within the requirement of Root Mean Square Error (RMSE) > 25m.</gco:CharacterString>
    </gmd:statement>
  </gmd:LI_Lineage>
</gmd:lineage>
</gmd:DQ_DataQuality>
</gmd:dataQualityInfo>
</gmd:MD_Metadata>

```

A.12.2 Dataset series

There is no significant difference between the metadata of a dataset and the metadata of a dataset series. See A.11.1.

A.12.3 Service

A.12.3.1 INSPIRE view

```

+ Part B 1 Identification:
+ Part B 1.1 Resource Title: Europe Mapping Service based on the Image2000 European mosaic (multispectral)
+ Part B 1.2 Resource Abstract: Map Service of a European Mosaic. The mosaic is a harmonised dataset and is based on the individual orthorectified scenes from the Image 2000 project. This service covers the Landsat 7 multispectral bands 4, 5 and 3
+ Part B 1.3 Resource Type: service
+ Part B 1.4 Resource Locator: http://image2000.jrc.it
+ Part B 1.4 Resource Locator: http://mapserver.jrc.it/wmsconnector/com.esri.wms.Esrimap/img2k_453_mos?request=getcapabilities&service=WMS
+ Part B 1.6 Coupled Resource:
+ ref: http://image2000.jrc.it/image2000_1_n12_multi
+ Part B 2 Classification of data and services:
+ Part B 2.2 Spatial data service type: View Service
+ Part B 3 Keyword:
+ Part B 3.1 Keyword value: earth observation
+ Part B 3 Keyword:
+ Part B 3.1 Keyword value: satellite imagery
+ Part B 3 Keyword:
+ Part B 3.1 Keyword value: humanGeographicViewer
+ Part B 4 Geographic Location:

```

- + **Part B 4.1 Bounding Box:**
 - + **West:** +3.93
 - + **East:** +7.57
 - + **North:** +52.10
 - + **South:** +54.10
- + **Part B 5 Temporal Reference:**
 - + **Part B 5.2 Date of publication:** 2005-12-14
- + **Part B 6 Quality and validity:**
 - + **Part B 7.1 Specification:**
 - + **title:** Service Abstract Test Suite
 - + **publication date:** 2007-11-21
 - + **Part B 7.2 Degree:** true
- + **Part B 8 Constraint related to access and use:**
 - + **Part B 8.1 Condition applying to access and use:** no condition apply
 - + **Part B 8.2 Limitation on public access:** no limitation on public access
- + **Part B 9 Responsible Organisation:**
 - + **Part B 9.1 Responsible party:**
 - + **organisation:** Joint Research Centre
 - + **e-mail:** image2000@jrc.it
 - + **Part B 9.2 Responsible party role:** publisher
- + **Part B 10 Metadata on metadata:**
 - + **Part B 10.1 Metadata point of contact:**
 - + **organisation:** Joint Research Centre
 - + **e-mail:** image2000@jrc.it
 - + **Part B 10.2 Metadata date:** 2005-12-14
 - + **Part B 10.3 Metadata language:** eng

A.12.3.2 ISO/TS 19139 XML File

```

<?xml version="1.0" encoding="UTF-8"?>
<gmd:MD_Metadata xsi:schemaLocation="http://www.isotc211.org/2005/srv
http://schemas.opengis.net/iso/19139/20060504/srv/srv.xsd" xmlns:srv="http://www.isotc211.org/2005/srv"
xmlns:gmd="http://www.isotc211.org/2005/gmd" xmlns:gco="http://www.isotc211.org/2005/gco"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:gml="http://www.opengis.net/gml"
xmlns:xlink="http://www.w3.org/1999/xlink">
  <gmd:fileIdentifier>
    <gco:CharacterString>2a83cb31-3331-4762-96d1-ff4acda68245</gco:CharacterString>
  </gmd:fileIdentifier>
  <gmd:language>
    <gmd:LanguageCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#LanguageCode" codeListValue="eng">eng</gmd:LanguageCode>
  </gmd:language>
  <gmd:hierarchyLevel>
    <gmd:MD_ScopeCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#MD_ScopeCode" codeListValue="service">service</gmd:MD_ScopeCode>
  </gmd:hierarchyLevel>
  <gmd:contact>
    <gmd:CI_ResponsibleParty>
      <gmd:organisationName>
        <gco:CharacterString>Joint Research Centre</gco:CharacterString>
      </gmd:organisationName>
      <gmd:contactInfo>
        <gmd:CI_Contact>
          <gmd:address>
            <gmd:CI_Address>
              <gmd:electronicMailAddress>
                <gco:CharacterString>image2000@jrc.it</gco:CharacterString>
              </gmd:electronicMailAddress>
            </gmd:CI_Address>
          </gmd:address>
        </gmd:CI_Contact>
      </gmd:contactInfo>
    </gmd:CI_ResponsibleParty>
  </gmd:contact>

```

```

    </gmd:CI_Contact>
  </gmd:contactInfo>
  <gmd:role>
    <gmd:CI_RoleCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#CI_RoleCode" codeListValue="pointOfContact">pointOfContact</gmd:CI_RoleCode>
    </gmd:role>
  </gmd:CI_ResponsibleParty>
</gmd:contact>
<gmd:dateStamp>
  <gco:Date>2005-12-14</gco:Date>
</gmd:dateStamp>
<gmd:metadataStandardName>
  <gco:CharacterString>ISO19119</gco:CharacterString>
</gmd:metadataStandardName>
<gmd:metadataStandardVersion>
  <gco:CharacterString>2005/PDAM 1</gco:CharacterString>
</gmd:metadataStandardVersion>
<gmd:identificationInfo>
  <srv:SV_ServiceIdentification>
    <gmd:citation>
      <gmd:CI_Citation>
        <gmd:title>
          <gco:CharacterString>Europe Mapping Service based on the Image2000 European mosaic
(multispectral)</gco:CharacterString>
        </gmd:title>
        <gmd:date>
          <gmd:CI_Date>
            <gmd:date>
              <gco:Date>2005-12-14</gco:Date>
            </gmd:date>
            <gmd:dateType>
              <gmd:CI_DateTypeCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#CI_DateTypeCode" codeListValue="publication">publication</gmd:CI_DateTypeCode>
            </gmd:dateType>
          </gmd:CI_Date>
        </gmd:date>
      </gmd:CI_Citation>
    </gmd:citation>
    <gmd:abstract>
      <gco:CharacterString>Map Service of a European Mosaic. The mosaic is a harmonised dataset and
is based on the individual orthorectified scenes from the Image 2000 project. This service covers the Landsat 7
multispectral bands 4, 5 and 3</gco:CharacterString>
    </gmd:abstract>
    <gmd:pointOfContact>
      <gmd:CI_ResponsibleParty>
        <gmd:organisationName>
          <gco:CharacterString>Joint Research Centre</gco:CharacterString>
        </gmd:organisationName>
        <gmd:contactInfo>
          <gmd:CI_Contact>
            <gmd:address>
              <gmd:CI_Address>
                <gmd:electronicMailAddress>
                  <gco:CharacterString>image2000@jrc.it</gco:CharacterString>
                </gmd:electronicMailAddress>
              </gmd:CI_Address>
            </gmd:address>
          </gmd:CI_Contact>
        </gmd:contactInfo>
        <gmd:role>
          <gmd:CI_RoleCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#CI_RoleCode" codeListValue="publisher">publisher</gmd:CI_RoleCode>
        </gmd:role>
      </gmd:CI_ResponsibleParty>
    </gmd:pointOfContact>
  </gmd:descriptiveKeywords>
  <gmd:MD_Keywords>
    <gmd:keyword>
      <gco:CharacterString>humanGeographicViewer</gco:CharacterString>
    </gmd:keyword>
    <gmd:keyword>
      <gco:CharacterString>satellite imagery</gco:CharacterString>
    </gmd:keyword>
    <gmd:keyword>
      <gco:CharacterString>earth observation</gco:CharacterString>
    </gmd:keyword>
  </gmd:MD_Keywords>

```



```

</gmd:MD_Keywords>
</gmd:descriptiveKeywords>
<gmd:resourceConstraints>
  <gmd:MD_Constraints>
    <gmd:useLimitation>
      <gco:CharacterString>no conditions apply</gco:CharacterString>
    </gmd:useLimitation>
  </gmd:MD_Constraints>
</gmd:resourceConstraints>
<gmd:resourceConstraints>
  <gmd:MD_LegalConstraints>
    <gmd:accessConstraints>
      <gmd:MD_RestrictionCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#MD_RestrictionCode"
codeListValue="otherRestrictions">otherRestrictions</gmd:MD_RestrictionCode>
    </gmd:accessConstraints>
    <gmd:otherConstraints>
      <gco:CharacterString>no limitations</gco:CharacterString>
    </gmd:otherConstraints>
  </gmd:MD_LegalConstraints>
</gmd:resourceConstraints>
<srv:serviceType>
  <gco:LocalName>view</gco:LocalName>
</srv:serviceType>
<srv:extent>
  <gmd:EX_Extent>
    <gmd:geographicElement>
      <gmd:EX_GeographicBoundingBox>
        <gmd:westBoundLongitude>
          <gco:Decimal>-3.93</gco:Decimal>
        </gmd:westBoundLongitude>
        <gmd:eastBoundLongitude>
          <gco:Decimal>7.57</gco:Decimal>
        </gmd:eastBoundLongitude>
        <gmd:southBoundLatitude>
          <gco:Decimal>52.10</gco:Decimal>
        </gmd:southBoundLatitude>
        <gmd:northBoundLatitude>
          <gco:Decimal>54.10</gco:Decimal>
        </gmd:northBoundLatitude>
      </gmd:EX_GeographicBoundingBox>
    </gmd:geographicElement>
  </gmd:EX_Extent>
</srv:extent>
<srv:couplingType gco:nilReason="missing"/>
<srv:containsOperations gco:nilReason="missing"/>
<srv:operatesOn xlink:href="http://image2000.jrc.it#image2000_1_nl2_multi"/>
</srv:SV_ServiceIdentification>
</gmd:identificationInfo>
<gmd:distributionInfo>
  <gmd:MD_Distribution>
    <gmd:distributionFormat>
      <gmd:MD_Format>
        <gmd:name gco:nilReason="inapplicable"/>
        <gmd:version gco:nilReason="inapplicable"/>
      </gmd:MD_Format>
    </gmd:distributionFormat>
    <gmd:transferOptions>
      <gmd:MD_DigitalTransferOptions>
        <gmd:onLine>
          <gmd:CI_OnlineResource>
            <gmd:linkage>
              <gmd:URL>http://image2000.jrc.it</gmd:URL>
            </gmd:linkage>
          </gmd:CI_OnlineResource>
        </gmd:onLine>
        <gmd:onLine>
          <gmd:CI_OnlineResource>
            <gmd:linkage>
              <gmd:URL>http://mapserver.jrc.it/wmsconnector/com.esri.wms.Esrimap/img2k_453_mos?request=getcapabilitie
s&amp;amp;service=WMS</gmd:URL>
            </gmd:linkage>
          </gmd:CI_OnlineResource>
        </gmd:onLine>
      </gmd:MD_DigitalTransferOptions>
    </gmd:transferOptions>
  </gmd:MD_Distribution>

```

```

</gmd:distributionInfo>
<gmd:dataQualityInfo>
  <gmd:DQ_DataQuality>
    <gmd:scope>
      <gmd:DQ_Scope>
        <gmd:level>
          <gmd:MD_ScopeCode codeListValue="service"
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#MD_ScopeCode">service</gmd:MD_ScopeCode>
          </gmd:level>
        </gmd:DQ_Scope>
      </gmd:scope>
    <gmd:report>
      <gmd:DQ_DomainConsistency>
        <gmd:result>
          <gmd:DQ_ConformanceResult>
            <gmd:specification>
              <gmd:CI_Citation>
                <gmd:title>
                  <gco:CharacterString>Service Abstract Test Suite</gco:CharacterString>
                </gmd:title>
                <gmd:date>
                  <gmd:CI_Date>
                    <gmd:date>
                      <gco:Date>2007-11-21</gco:Date>
                    </gmd:date>
                    <gmd:dateType>
                      <gmd:CI_DateTypeCode
codeList="http://standards.iso.org/ittf/PubliclyAvailableStandards/ISO_19139_Schemas/resources/Codelist/ML_gmx
Codelists.xml#CI_DateTypeCode" codeListValue="publication">publication</gmd:CI_DateTypeCode>
                      </gmd:dateType>
                    </gmd:CI_Date>
                  </gmd:date>
                </gmd:CI_Citation>
              </gmd:specification>
            <gmd:explanation>
              <gco:CharacterString>See the referenced specification</gco:CharacterString>
            </gmd:explanation>
            <gmd:pass>
              <gco:Boolean>true</gco:Boolean>
            </gmd:pass>
          </gmd:DQ_ConformanceResult>
        </gmd:result>
      </gmd:DQ_DomainConsistency>
    </gmd:report>
  </gmd:DQ_DataQuality>
</gmd:dataQualityInfo>
</gmd:MD_Metadata>

```